

The Embedded I/O Company



TDRV018-SW-42

VxWorks Device Driver

Reconfigurable FPGA

Version 1.1.x

User Manual

Issue 1.1.1

September 2021

powerBridge
Computer 

Ehlbeek 15a
30938 Burgwedel
fon 05139-9980-0
fax 05139-9980-49

www.powerbridge.de
info@powerbridge.de

TEWS TECHNOLOGIES GmbH

Am Bahnhof 7 25469 Halstenbek, Germany
9 (0) 4101 4058 0 Fax: +49 (0) 4101 4058 19
il: info@tews.com www.tews.com

TDRV018-SW-42

VxWorks Device Driver

FPGA Platform Example Application

Supported Modules:

TPMC634
 TXMC633
 TXMC635
 TXMC637
 TXMC638
 TPCE636

This document contains information, which is proprietary to TEWS TECHNOLOGIES GmbH. Any reproduction without written permission is forbidden.

TEWS TECHNOLOGIES GmbH has made any effort to ensure that this manual is accurate and complete. However TEWS TECHNOLOGIES GmbH reserves the right to change the product described in this document at any time without notice.

TEWS TECHNOLOGIES GmbH is not liable for any damage arising out of the application or use of the device described herein.

©2015-2021 by TEWS TECHNOLOGIES GmbH

Issue	Description	Date
1.0.0	First Issue	December 17, 2015
1.1.0	Installation description removed (refer to Installation Manual) Support for new hardware added, API extended	May 22, 2020
1.1.1	TXMC637 added	September 1, 2021

Table of Contents

1	INTRODUCTION.....	5
1.1	Device Driver	5
2	API DOCUMENTATION	7
2.1	General Functions.....	7
2.1.1	tdrv018Open	7
2.1.2	tdrv018Close.....	9
2.1.3	tdrv018GetPciInfo	11
2.1.4	tdrv018GetBoardInfo	13
2.1.5	tdrv018GetBoardName.....	15
2.1.6	tdrv018GetBoardSerial	17
2.1.7	tdrv018GetBoardFWVersion	19
2.1.8	tdrv018GetFpgaStatus	21
2.2	Local Bus Control Functions.....	23
2.2.1	tdrv018LocalBusControl	23
2.2.2	tdrv018LocalBusStatus.....	25
2.3	EEPROM Access Functions.....	27
2.3.1	tdrv018EepromWrite.....	27
2.3.2	tdrv018EepromRead.....	29
2.4	Pull-Resistor Configuration Functions	31
2.4.1	tdrv018PullConfigSet.....	31
2.4.2	tdrv018PullConfigGet.....	33
2.5	FPGA Programming Functions	35
2.5.1	tdrv018ProgSpiFlashFromFile.....	35
2.5.2	tdrv018ProgSpiFlash	37
2.5.3	tdrv018ProgFpgaFromFile.....	39
2.5.4	tdrv018ProgFpga	41
2.5.5	tdrv018ConfigFromSpiFlash	43
2.5.6	tdrv018PcieLinkEnable.....	45
2.5.7	tdrv018PcieLinkDisable	47
2.5.8	tdrv018RestorePciHeader	49
2.6	Register Access Functions.....	51
2.6.1	tdrv018Read8	51
2.6.2	tdrv018ReadBE16	54
2.6.3	tdrv018ReadLE16.....	57
2.6.4	tdrv018ReadBE32	60
2.6.5	tdrv018ReadLE32.....	63
2.6.6	tdrv018Write8	66
2.6.7	tdrv018WriteBE16.....	69
2.6.8	tdrv018WriteLE16	72
2.6.9	tdrv018WriteBE32.....	75
2.6.10	tdrv018WriteLE32.....	78
2.7	Resource Mapping Functions.....	81
2.7.1	tdrv018PciResourceMap	81
2.7.2	tdrv018PciResourceUnmap.....	84
2.8	Interrupt Functions	86
2.8.1	tdrv018InterruptWait	86
2.8.2	tdrv018InterruptRegisterCallbackThread.....	89
2.8.3	tdrv018InterruptUnregisterCallback.....	96
2.8.4	tdrv018InterruptConfig.....	98
2.9	Endian Conversion Functions	103
2.9.1	endian_be16.....	103

2.9.2	endian_le16	104
2.9.3	endian_be32	105
2.9.4	endian_le32	106
3	DEBUGGING AND DIAGNOSTIC	107

1 Introduction

1.1 Device Driver

The TDRV018-SW-42 VxWorks device driver software allows the operation of the supported hardware modules conforming to the VxWorks I/O system specification.

The TDRV018-SW-42 release contains independent driver sources for the old legacy (pre-VxBus) and the new VxBus-enabled driver model. The VxBus-enabled driver is recommended for new developments with later VxWorks 6.x release and mandatory for VxWorks 64-bit and SMP systems

The driver provides an application programming interface (API) which allows OS independent access to the devices for compatibility between different OS versions and OS.

The TDRV018-SW-42 device driver supports the following features:

- Program onboard SPI Flash, initiate FPGA reconfiguration
- Program onboard FPGA directly
- Read/write FPGA registers (32bit / 16bit / 8bit)
- Read/write specific PCI Configuration EEPROM registers
- Wait for interrupts
- Register Callback functions for interrupt handling
- Driver functions (except for SPI/FPGA programming) are thread-safe, as long as unique handles are used.

The TDRV018-SW-42 supports the modules listed below:

TPMC634	Reconfigurable FPGA	PMC
TXMC633	Reconfigurable FPGA with 64 TTL I/O / 32 Differential I/O Lines	XMC
TXMC635	Reconfigurable FPGA with 48 x TTL IO / 32 x 16 Bit Analog In / 8 x 16 Bit Analog Out	XMC
TXMC637	Reconfigurable FPGA with 16 x 16 Bit Analog Input / 8 x 16 Bit Analog Output / 32 digital I/O	XMC
TXMC638	Reconfigurable FPGA with 24 x 16 Bit Analog Input	XMC
TPCE636	Reconfigurable FPGA with 16 x 16 Bit Analog Input / 16 x 16 Bit Analog Output	PCIe

In this document all supported modules and devices will be called TDRV018. Specials for a certain device will be advised.

To get more information about the features and use of supported devices it is recommended to read the manuals listed below.

TEWS TECHNOLOGIES VxWorks Device Drivers - Installation Guide
TPMC634 (or compatible) User Manual
TXMC633, TXMC635, TXMC637, TXMC638 (or compatible) User Manual
TPCE636 (or compatible) User Manual

2 API Documentation

2.1 General Functions

2.1.1 tdrv018Open

NAME

tdrv018Open – open a device.

SYNOPSIS

```
TDRV018_HANDLE tdrv018Open  
(  
    char      *DeviceName  
)
```

DESCRIPTION

Before I/O can be performed to a device, a device handle must be opened by a call to this function. If the legacy TDRV018 driver is used, this function will also install the legacy driver and create devices with the first call. The VxBus TDRV018 driver will be installed automatically by the VxBus system.

The tdrv018Open function can be called multiple times (e.g. in different tasks)

PARAMETERS

DeviceName

This parameter points to a null-terminated string that specifies the name of the device. The first TDRV018 device is named "/tdrv018/0" the second device is named "/tdrv018/1" and so on.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;

/*
** open the specified device
*/
hdl = tdrv018Open("/tdrv018/0");
if (hdl == NULL)
{
    /* handle open error */
}
```

RETURNS

A device handle, or NULL if the function fails. An error code will be stored in *errno*.

ERROR CODES

The error codes are stored in *errno*.

The error code is a standard error code set by the I/O system.

2.1.2 tdrv018Close

NAME

tdrv018Close – close a device.

SYNOPSIS

```
TDRV018_STATUS tdrv018Close
(
    TDRV018_HANDLE    hdl
)
```

DESCRIPTION

This function closes a previously opened device.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** close the device
*/
result = tdrv018Close(hdl);
if (result != TDRV018_OK)
{
    /* handle close error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid

2.1.3 tdrv018GetPciInfo

NAME

tdrv018GetPciInfo – get information of the module PCI header

SYNOPSIS

```
TDRV018_STATUS tdrv018GetPciInfo
(
    TDRV018_HANDLE          hdl,
    TDRV018_PCIINFO_BUF    *pPciInfoBuf
)
```

DESCRIPTION

This function returns information of the module PCI header in the provided data buffer.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pPciInfoBuf

This argument is a pointer to the structure TDRV018_PCIINFO_BUF that receives information of the module PCI header.

```
typedef struct
{
    unsigned short    vendorId;
    unsigned short    deviceId;
    unsigned short    subSystemId;
    unsigned short    subSystemVendorId;
    int               pciBusNo;
    int               pciDevNo;
    int               pciFuncNo;
} TDRV018_PCIINFO_BUF;
```

vendorId

PCI module vendor ID.

deviceId

PCI module device ID

subSystemId
PCI module sub system ID

subSystemVendorId
PCI module sub system vendor ID

pciBusNo
Number of the PCI bus, where the module resides.

pciDevNo
PCI device number

pciFuncNo
PCI function number

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE      hdl;
TDRV018_STATUS      result;
TDRV018_PCIINFO_BUF pciInfoBuf

/*
** get module PCI information
*/
result = tdrv018GetPciInfo(hdl, &pciInfoBuf);

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid

2.1.4 tdrv018GetBoardInfo

NAME

tdrv018GetBoardInfo – get information of the board

SYNOPSIS

```
TDRV018_STATUS tdrv018GetBoardInfo
(
    TDRV018_HANDLE          hdl,
    unsigned int            *pFpgaStatus,
    unsigned int            *pDipSwitch,
    unsigned int            *pFirmwareVersion
)
```

DESCRIPTION

This function returns information about the board status. This function is only supported for TPMC634 devices.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pFpgaStatus

This argument returns the current FPGA Status. The following values are possible:

Value	Description
TDRV018_FPGASTAT_DONE	DONE Signal State
TDRV018_FPGASTAT_INIT	INIT Signal State

pDipSwitch

This argument returns the value of the onboard 4-bit DIP switch. Bit 0 corresponds to DIP switch position 1, bit 1 corresponds to DIP switch position 2 and so on.

pFirmwareVersion

This argument returns the firmware version of the PCI target device.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE          hdl;
TDRV018_STATUS          result;
unsigned int            FpgaStatus;
unsigned int            DipSwitch;
unsigned int            FWVersion;

/*
** get board information
*/
result = tdrv018GetBoardInfo( hdl, &FpgaStatus, &DipSwitch, &FWVersion );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.1.5 tdrv018GetBoardName

NAME

tdrv018GetBoardName – get Name of the board

SYNOPSIS

```
TDRV018_STATUS tdrv018GetBoardName
(
    TDRV018_HANDLE          hdl,
    unsigned char           *pBoardName,
    int                     len
)
```

DESCRIPTION

This function returns the name of the board to distinguish between the supported hardware modules and devices.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pBoardName

This argument returns a null-terminated ASCII string describing the specific hardware module. The following boarding naming scheme is implemented:

Value	Description
"TPMC634"	TPMC634 Device
"TXMC633-BCC"	TXMC633 BCC Device
"TXMC633-FPGA"	TXMC633 User-FPGA Device

len

This argument specifies the maximum length available for storing the board name.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE      hdl;
TDRV018_STATUS      result;
char                BoardName[40];

/*
** get board name
*/
result = tdrv018GetBoardName( hdl, &BoardName, 40 );

if (result == TDRV018_OK)
{
    printf("Board Name: %s\n", BoardName);
} else {
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid

2.1.6 tdrv018GetBoardSerial

NAME

tdrv018GetBoardSerial – get Serial Number of the board

SYNOPSIS

```
TDRV018_STATUS tdrv018GetBoardSerial
(
    TDRV018_HANDLE    hdl,
    unsigned int      *pSerialNumber
)
```

DESCRIPTION

This function returns the serial number of the board. This function is only supported by BCC devices.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pSerialNumber

This argument returns the board serial number as a decimal number.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE      hdl;
TDRV018_STATUS      result;
unsigned int         SerialNumber;

/*
** get board serial number
*/
result = tdrv018GetBoardSerial( hdl, &SerialNumber );

if (result == TDRV018_OK)
{
    printf("Board Serial Number: %d\n", SerialNumber);
} else {
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.1.7 tdrv018GetBoardFWVersion

NAME

tdrv018GetBoardFWVersion – get Firmware Version of the board

SYNOPSIS

```
TDRV018_STATUS tdrv018GetBoardFWVersion  
(  
    TDRV018_HANDLE          hdl,  
    unsigned int            *pFWVersion  
)
```

DESCRIPTION

This function returns the Firmware Version of the board. This function is not supported by User-FPGA devices.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pFWVersion

This argument returns the Firmware Version of the device. For details, please refer to the corresponding hardware user manual.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE      hdl;
TDRV018_STATUS      result;
unsigned int        FWVersion;

/*
** get board serial number
*/
result = tdrv018GetBoardFWVersion( hdl, &FWVersion );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.1.8 tdrv018GetFpgaStatus

NAME

tdrv018GetFpgaStatus – get status of the User-FPGA

SYNOPSIS

```
TDRV018_STATUS tdrv018GetFpgaStatus
(
    TDRV018_HANDLE          hdl,
    unsigned int            *pFpgaStatus
)
```

DESCRIPTION

This function returns the configuration status of the User-FPGA. This function is not supported by User-FPGA devices.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pFpgaStatus

This argument returns the current FPGA Status. The following values are possible:

Value	Description
TDRV018_FPGASTAT_DONE	DONE Signal State
TDRV018_FPGASTAT_INIT	INIT Signal State

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE      hdl;
TDRV018_STATUS      result;
unsigned int         FpgaStatus;

/*
** get FPGA Status
*/
result = tdrv018GetFpgaStatus( hdl, &FpgaStatus );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.2 Local Bus Control Functions

2.2.1 tdrv018LocalBusControl

NAME

tdrv018LocalBusControl – Configure and control the Local Bus

SYNOPSIS

```
TDRV018_STATUS tdrv018LocalBusControl
(
    TDRV018_HANDLE    hdl,
    unsigned int      ControlFlags
)
```

DESCRIPTION

This function controls the Local Bus Interface.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

ControlFlags

This value specifies a 32bit unsigned int value, which contains the combined Local Bus Control Flags. The following OR'ed values are possible:

Value	Description
TDRV018_LOCALBUS_RESET	If set, the Local Bus Reset signal is asserted.
TDRV018_LOCALBUS_TOUT_DIS	If set, the Local Bus Timeout is disabled.
TDRV018_LOCALBUS_PLLRESET	If set, the Local Bus PLL is held in reset mode.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Perform a Local Bus Reset
*/
/* assert Local Bus Reset */
result = tdrv018LocalBusControl( hdl, TDRV018_LOCALBUS_RESET );
if (result != TDRV018_OK)
{
    /* handle error */
}

... wait some time ...

/* de-assert Local Bus Reset */
result = tdrv018LocalBusControl( hdl, 0 );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_INVALID	The specified flags are invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.2.2 tdrv018LocalBusStatus

NAME

tdrv018LocalBusStatus – Read Status of the Local Bus

SYNOPSIS

```
TDRV018_STATUS tdrv018LocalBusStatus
(
    TDRV018_HANDLE    hdl,
    unsigned int      *pStatus
)
```

DESCRIPTION

This function reads the status of the Local Bus Interface. The event flags are cleared after execution of this function.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pStatus

This argument returns the Local Bus Status and Event Flags. The following OR'ed values are possible:

Value	Description
TDRV018_LOCALBUS_PLLLOCKED	The PLL is currently locked.
TDRV018_LOCALBUS_RESEACTIVE	The Local Bus Reset is currently active.
TDRV018_LOCALBUS_MASTERABORT	A Master Abort has been detected.
TDRV018_LOCALBUS_TARGETERROR	A Target Error has been detected.
TDRV018_LOCALBUS_PLLLOSSOFLOCK	A Loss-of-Lock has been detected.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned int       Status;

/*
** Check the Local Bus Status
*/
result = tdrv018LocalBusStatus( hdl, &Status );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.3 EEPROM Access Functions

2.3.1 tdrv018EepromWrite

NAME

tdrv018EepromWrite – Write 16bit value to PCI Configuration EEPROM

SYNOPSIS

```
TDRV018_STATUS tdrv018EepromWrite
(
    TDRV018_HANDLE    hdl,
    unsigned int      Offset,
    unsigned short     Value
)
```

DESCRIPTION

This function writes an *unsigned short* (16bit) value to a specific PCI Configuration EEPROM memory offset.

Please note that the PCI target device reloads the new configuration from the EEPROM after a PCI reset, i.e. the system must be rebooted to make the changes take effect.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Offset

Specifies the offset into the PCI Configuration EEPROM, where the supplied data word should be written. The offset must be specified as word-address.

Following offsets are available:

Offset	Access
00h – 01h	R
02h – 7Fh	R / W

Refer to the TPMC634 User Manual for detailed information on these registers.

Value

This value specifies a 16bit word that should be written to the specified offset.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned int      Offset;
unsigned short     Value;

/*
** Change the Subsystem Vendor ID to TEWS TECHNOLOGIES (0x1498)
*/
Offset = 0x05;
Value  = 0x1498;

result = tdrv018EepromWrite( hdl, Offset, Value );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_INVALID	The specified offset is invalid, or read-only.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.3.2 tdrv018EepromRead

NAME

tdrv018EepromRead – Read 16bit value from PCI Configuration EEPROM

SYNOPSIS

```
TDRV018_STATUS tdrv018EepromRead
(
    TDRV018_HANDLE    hdl,
    unsigned int      Offset,
    unsigned short    *pValue
)
```

DESCRIPTION

This function reads an *unsigned short* (16bit) value from a specific PCI Configuration EEPROM memory offset.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Offset

Specifies the offset into the PCI Configuration EEPROM, where the supplied data word should be written. The offset must be specified as word-address.

Following offsets are available:

Offset	Access
00h – 01h	R
02h – 7Fh	R / W

Refer to the TPMC634 User Manual for detailed information on these registers.

pValue

This value is a pointer to an *unsigned short* value, which receives the 16bit word.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned int       Offset;
unsigned short     Value;

/*
** Read Subsystem ID
*/
Offset = 0x04;

result = tdrv018EepromRead( hdl, Offset, &Value );
if (result == TDRV018_OK)
{
    printf( "Value = 0x%04X\n", Value );
} else {
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_INVALID	The specified offset is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.4 Pull-Resistor Configuration Functions

The Pull-Resistor Configuration Functions are only supported for TXMC633 and TXMC635 (or compatible) BCC devices.

2.4.1 tdrv018PullConfigSet

NAME

tdrv018PullConfigSet – Configure the pull-resistor settings

SYNOPSIS

```
TDRV018_STATUS tdrv018PullConfigSet
(
    TDRV018_HANDLE    hdl,
    int               PullControl,
    unsigned int      PullConfig
)
```

DESCRIPTION

This function writes the configuration value into the Pull Resistor Configuration Register of the selected device.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

PullControl

This parameter specifies if the Pull-Resistor Configuration shall be controlled by the User-FPGA or by the PullConfig value. The following values are possible:

Value	Description
TDRV018_PULLCNT_USERFPGA	Pull-Configuration is controlled by the User-FPGA
TDRV018_PULLCNT_BCC	Pull-Configuration is controlled by the BCC and the PullConfig value.

PullConfig

This value specifies a 32bit unsigned int value, which directly corresponds to the Pull Resistor Configuration Register of the supported hardware module. For details, please refer to the corresponding hardware user-manual.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Set the pull-resistor configuration
*/
result = tdrv018PullConfigSet( hdl, TDRV018_PULLCNT_BCC, 0x000000AA );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.4.2 tdrv018PullConfigGet

NAME

tdrv018PullConfigGet – Read the current pull-resistor configuration

SYNOPSIS

```
TDRV018_STATUS tdrv018PullConfigGet
(
    TDRV018_HANDLE    hdl,
    int                *pPullControl,
    unsigned int       *pPullConfig
)
```

DESCRIPTION

This function reads the configuration value from the Pull Resistor Configuration Register of the selected device.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pPullControl

This parameter specifies if the Pull-Resistor Configuration is controlled by the User-FPGA or by the PullConfig value. The following values are possible:

Value	Description
TDRV018_PULLCNT_USERFPGA	Pull-Configuration is controlled by the User-FPGA
TDRV018_PULLCNT_BCC	Pull-Configuration is controlled by the BCC and the PullConfig value.

pPullConfig

This value specifies a pointer to a 32bit unsigned int value, which receives the content of the Pull Resistor Configuration Register of the supported hardware module. For details, please refer to the corresponding hardware user-manual.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               PullControl;
unsigned int      PullConfig;

/*
** Read the pull-resistor configuration
*/
result = tdrv018PullConfigGet( hdl, &PullControl, &PullConfig );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.5 FPGA Programming Functions

2.5.1 tdrv018ProgSpiFlashFromFile

NAME

tdrv018ProgSpiFlashFromFile – Program the SPI Flash from a supplied bitstream file

SYNOPSIS

```
TDRV018_STATUS tdrv018ProgSpiFlashFromFile  
(  
    TDRV018_HANDLE    hdl,  
    char              *pFilename  
)
```

DESCRIPTION

This function writes the content of a supplied binary configuration bitstream file (.bin) into the onboard SPI configuration flash. The SPI flash is erased first, which might take up to 120 seconds. The FPGA is not affected by this function. To initiate the FPGA configuration, use the function `tdrv018ConfigFromSpiFlash()`.

Only one programming function may be executed at once.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pFilename

This value is a pointer to a null-terminated character string, specifying the binary configuration bitstream file name (.bin).

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Program the SPI Configuration Flash from a file
*/
result = tdrv018ProgSpiFlashFromFile( hdl, "tpmc634fpga.bin" );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_IO	Error during SPI transfer

2.5.2 tdrv018ProgSpiFlash

NAME

tdrv018ProgSpiFlash – Program the SPI Flash

SYNOPSIS

```
TDRV018_STATUS tdrv018ProgSpiFlash
(
    TDRV018_HANDLE    hdl,
    unsigned char     *pData,
    unsigned int       numBytes
)
```

DESCRIPTION

This function writes supplied configuration data into the onboard SPI configuration flash. The SPI flash is erased first, which might take up to 120 seconds. The FPGA is not affected by this function. To initiate the FPGA configuration, use the function `tdrv018ConfigFromSpiFlash()`.

Only one programming function may be executed at once.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pData

This value is a pointer to the configuration data, residing in memory.

numBytes

This value specifies the number of bytes to be written into the SPI flash.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned char      *pData;
unsigned int       numBytes;

/*
** Program the SPI Configuration Flash from a memory location
*/

/* allocate and fill the memory area */
numBytes = ...;
pData = (unsigned char*)malloc( numBytes );
...

result = tdrv018ProgSpiFlash( hdl, pData, numBytes );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_IO	Error during SPI transfer

2.5.3 tdrv018ProgFpgaFromFile

NAME

tdrv018ProgFpgaFromFile – Program the FPGA from a supplied bitstream file using Select Map

SYNOPSIS

```
TDRV018_STATUS tdrv018ProgFpgaFromFile
(
    TDRV018_HANDLE    hdl,
    char              *pFilename
    int               timeout
)
```

DESCRIPTION

This function writes the content of a supplied configuration bitstream file directly into the FPGA using Select Map. The FPGA is not functional during the programming process.

Only one programming function may be executed at once.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pFilename

This value is a pointer to a null-terminated character string, specifying the configuration bitstream file name.

timeout

This value specifies the timeout in milliseconds the function will wait for the FPGA loading to finish, i.e. the DONE signal switches to HIGH. The granularity depends on the operating system. To wait indefinitely, specify -1 as timeout parameter.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Directly program the FPGA from a file, wait up to 1 second for DONE
*/
result = tdrv018ProgFpgaFromFile( hdl, "tpmc634fpga.bin", 1000 );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_IO	Error during FPGA Configuration. DONE remained LOW.

2.5.4 tdrv018ProgFpga

NAME

tdrv018ProgFpga – Program the FPGA using Select Map

SYNOPSIS

```
TDRV018_STATUS tdrv018ProgFpga
(
    TDRV018_HANDLE    hdl,
    unsigned char      *pData,
    unsigned int       numBytes,
    int                timeout
)
```

DESCRIPTION

This function writes the content of a supplied configuration bitstream file directly into the FPGA using Select Map. The FPGA is not functional during the programming process.

Only one programming function may be executed at once.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pFilename

This value is a pointer to a null-terminated character string, specifying the configuration bitstream file name.

pData

This value is a pointer to the configuration data, residing in memory.

numBytes

This value specifies the number of bytes to be written into the FPGA.

timeout

This value specifies the timeout in milliseconds the function will wait for the FPGA loading to finish, i.e. the DONE signal switches to HIGH. The granularity depends on the operating system. To wait indefinitely, specify -1 as timeout parameter.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned char      *pData;
unsigned int       numBytes;

/*
** Directly program the FPGA, wait up to 1 second for DONE
*/
/* allocate and fill the memory area */
numBytes = ...;
pData = (unsigned char*)malloc( numBytes );
...

result = tdrv018ProgFpga( hdl, pData, numBytes, 1000 );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_IO	Error during FPGA Configuration. DONE remained LOW.

2.5.5 tdrv018ConfigFromSpiFlash

NAME

tdrv018ConfigFromSpiFlash – Start loading the FPGA from the SPI Flash

SYNOPSIS

```
TDRV018_STATUS tdrv018ConfigFromSpiFlash
(
    TDRV018_HANDLE    hdl,
    int               timeout
)
```

DESCRIPTION

This function starts loading the FPGA bitstream from the SPI Flash into the FPGA.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

timeout

This value specifies the timeout in milliseconds the function will wait for the FPGA loading to finish, i.e. the DONE signal switches to HIGH. The granularity depends on the operating system. To wait indefinitely, specify -1 as timeout parameter.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Load the FPGA from the SPI Flash, wait up to 1 second for DONE
*/
result = tdrv018ConfigFromSpiFlash( hdl, 1000 );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_IO	Error during FPGA Configuration. DONE remained LOW.

2.5.6 tdrv018PcieLinkEnable

NAME

tdrv018PcieLinkEnable – Enable PCIe Link for the User-FPGA

SYNOPSIS

```
TDRV018_STATUS tdrv018PcieLinkEnable
(
    TDRV018_HANDLE    hdl
)
```

DESCRIPTION

This function gracefully enables the PCIe Link for the User-FPGA. This function is only supported by BCC devices. Reconfiguring a User-FPGA might result in PCIe errors, which might cause unpredictable behavior of the overall system.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Enable the PCIe Link of the User-FPGA
*/
result = tdrv018PcieLinkEnable( hdl );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.5.7 tdrv018PcieLinkDisable

NAME

tdrv018PcieLinkDisable – Disable PCIe Link for the User-FPGA

SYNOPSIS

```
TDRV018_STATUS tdrv018PcieLinkDisable
(
    TDRV018_HANDLE    hdl
)
```

DESCRIPTION

This function gracefully disables the PCIe Link for the User-FPGA. This function is only supported by BCC devices. Reconfiguring a User-FPGA might result in PCIe errors, which might cause unpredictable behavior of the overall system. So before starting a configuration which might affect the PCIe Link State of the User-FPGA, disabling the PCIe link is suggested.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Disable the PCIe Link of the User-FPGA
*/
result = tdrv018PcieLinkDisable( hdl );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.5.8 tdrv018RestorePciHeader

NAME

tdrv018RestorePciHeader – Restore the PCI header of the User-FPGA

SYNOPSIS

```
TDRV018_STATUS tdrv018RestorePciHeader
(
    TDRV018_HANDLE    hdl
)
```

DESCRIPTION

This function restores the PCI header of the User-FPGA using values stored upon driver start. The PCI resources of the new User-FPGA design must match the resource configuration of the initially stored PCI header, so changing the number or size of PCI resources for the new User-FPGA design is not possible. After reconfiguration of a User-FPGA, the PCI header configuration is lost. To allow further accesses to the User-FPGA, the PCI header must be restored using this function.

This function is only supported by User-FPGA devices.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;

/*
** Restore the PCI header of the User-FPGA
*/
result = tdrv018RestorePciHeader( hdl );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.6 Register Access Functions

2.6.1 tdrv018Read8

NAME

tdrv018Read8 – read 8-bit values from PCI BAR space

SYNOPSIS

```
TDRV018_STATUS tdrv018Read8
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    int               offset,
    int               numItems,
    unsigned char     *pData
)
```

DESCRIPTION

This function reads the specified number of items from the PCI BAR space by using single byte (8-bit) accesses.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (8-bit) to read.

pData

This argument is a pointer to an unsigned char buffer which will be filled with the specified number of items from the PCI BAR space. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 256

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned char      dataBuf[NUM_ITEMS];

offset = 0x0000;
/*
** read 256 Bytes from the User FPGA Register Area
*/
result = tdrv018Read8( hdl, TDRV018_RES_MEM_3,
                      offset, NUM_ITEMS, dataBuf );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVAL	The specified access range exceeds PCI BAR limits

2.6.2 tdrv018ReadBE16

NAME

tdrv018ReadBE16 – read 16-bit values from PCI BAR space, Big Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018ReadBE16
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    int               offset,
    int               numItems,
    unsigned short    *pData
)
```

DESCRIPTION

This function reads the specified number of items from the PCI BAR space by using 16-bit accesses. The values are returned as Big Endian values, that means on Intel x86 architectures the multibyte data will be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (16-bit) to read.

pData

This argument is a pointer to an unsigned short buffer which will be filled with the specified number of items from the PCI BAR space. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 128

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned short    dataBuf[NUM_ITEMS];

offset = 0x00;
/*
** read 256 Bytes from the User FPGA Register Area
*/
result = tdrv018ReadBE16(    hdl, TDRV018_RES_MEM_3,
                            offset, NUM_ITEMS, dataBuf );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVAL	The specified access range exceeds PCI BAR limits

2.6.3 tdrv018ReadLE16

NAME

tdrv018ReadLE16 – read 16-bit values from PCI BAR space, Little Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018ReadLE16
(
    TDRV018_HANDLE    hdl,
    int                pciResource,
    int                offset,
    int                numItems,
    unsigned short    *pData
)
```

DESCRIPTION

This function reads the specified number of items from the PCI BAR space by using 16-bit accesses. The values are returned as Little Endian values, that means on Intel x86 architectures the multibyte data will not be byte-swapped.

The register sets of FPGA onchip bus slave devices and DRAM memory areas can be accessed via addressable data regions in PCI BAR space.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (16-bit) to read.

pData

This argument is a pointer to an unsigned short buffer which will be filled with the specified number of items from the PCI BAR space. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 128

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned short    dataBuf[NUM_ITEMS];

offset = 0x00;
/*
** read 256 Bytes from the User FPGA Register Area
*/
result = tdrv018ReadLE16(    hdl, TDRV018_RES_MEM_3,
                           offset, NUM_ITEMS, dataBuf );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVALID	The specified access range exceeds PCI BAR limits

2.6.4 tdrv018ReadBE32

NAME

tdrv018ReadBE32 – read 32-bit values from PCI BAR space, Big Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018ReadBE32
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    int               offset,
    int               numItems,
    unsigned int      *pData
)
```

DESCRIPTION

This function reads the specified number of items from the PCI BAR space by using 32-bit accesses. The values are returned as Big Endian values, that means on Intel x86 architectures the multibyte data will be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (32-bit) to read.

pData

This argument is a pointer to an unsigned int buffer which will be filled with the specified number of items from the PCI BAR space. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 2

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned int      dataBuf[NUM_ITEMS];

offset = 0x00;
/*
** read I/O Input Registers of the FPGA Example Design
*/
result = tdrv018ReadBE32(    hdl, TDRV018_RES_MEM_3,
                           offset, NUM_ITEMS, dataBuf );
if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVALID	The specified access range exceeds PCI BAR limits

2.6.5 tdrv018ReadLE32

NAME

tdrv018ReadLE32 – read 32-bit values from PCI BAR space, Little Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018ReadLE32
(
    TDRV018_HANDLE    hdl,
    int                pciResource,
    int                offset,
    int                numItems,
    unsigned int       *pData
)
```

DESCRIPTION

This function reads the specified number of items from the PCI BAR space by using 32-bit accesses. The values are returned as Little Endian values, that means on Intel x86 architectures the multibyte data will not be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (32-bit) to read.

pData

This argument is a pointer to an unsigned int buffer which will be filled with the specified number of items from the PCI BAR space. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 2

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned int      dataBuf[NUM_ITEMS];

offset = 0x00;
/*
** read I/O Input Registers of the FPGA Example Design
*/
result = tdrv018ReadLE32(    hdl, TDRV018_RES_MEM_3,
                           offset, NUM_ITEMS, dataBuf );
if (result != TDRV018_OK)
{
    /* handle error */
}
```


RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVALID	The specified access range exceeds PCI BAR limits

2.6.6 tdrv018Write8

NAME

tdrv018Write8 – write 8-bit values to the PCI BAR space

SYNOPSIS

```
TDRV018_STATUS tdrv018Write8
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    int               offset,
    int               numItems,
    unsigned char     *pData
)
```

DESCRIPTION

This function writes the specified number of items to the PCI BAR space by using single byte (8-bit) accesses.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (8-bit) to write.

pData

This argument is a pointer to an unsigned char buffer with the data items to write. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 4

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned char     dataBuf[NUM_ITEMS];

dataBuf[0] = 0xAA;
dataBuf[1] = 0x55;
...

offset = 0xF8;
/*
** write 4 bytes to a 32bit Scratchpad Register
*/
result = tdrv018Write8( hdl, TDRV018_RES_MEM_3,
                       offset, NUM_ITEMS, dataBuf );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVAL	The specified access range exceeds PCI BAR limits

2.6.7 tdrv018WriteBE16

NAME

tdrv018WriteBE16 – write 16-bit values to the PCI BAR space, Big Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018WriteBE16
(
    TDRV018_HANDLE    hdl,
    int                pciResource,
    int                offset,
    int                numItems,
    unsigned short    *pData
)
```

DESCRIPTION

This function writes the specified number of items to the PCI BAR space by using 16-bit accesses.

The values are written in Big Endian Mode, that means on Intel x86 architectures the multibyte data will be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (16-bit) to write.

pData

This argument is a pointer to an unsigned short buffer with the data items to write. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 2

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned short     dataBuf[NUM_ITEMS];

dataBuf[0] = 0xAA55;
dataBuf[1] = 0x55AA;
...

offset = 0xF8;
/*
** write 2 datawords to a 32bit Scratchpad Register
*/
result = tdrv018WriteBE16( hdl, TDRV018_RES_MEM_3,
                          offset, NUM_ITEMS, dataBuf );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVAL	The specified access range exceeds PCI BAR limits

2.6.8 tdrv018WriteLE16

NAME

tdrv018WriteLE16 – write 16-bit values to the PCI BAR space, Little Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018WriteLE16
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    int               offset,
    int               numItems,
    unsigned short    *pData
)
```

DESCRIPTION

This function writes the specified number of items to the PCI BAR space by using 16-bit accesses.

The values are written in Little Endian Mode, that means on Intel x86 architectures the multibyte data will not be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (16-bit) to write.

pData

This argument is a pointer to an unsigned short buffer with the data items to write. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

#define NUM_ITEMS 2

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned short    dataBuf[NUM_ITEMS];

dataBuf[0] = 0xAA55;
dataBuf[1] = 0x55AA;
...

offset = 0xF8;
/*
** write 2 data words to a 32bit Scratchpad Register
*/
result = tdrv018WriteLE16( hdl, TDRV018_RES_MEM_3,
                          offset, NUM_ITEMS, dataBuf );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVAL	The specified access range exceeds PCI BAR limits

2.6.9 tdrv018WriteBE32

NAME

tdrv018WriteBE32 – write 32-bit values to the PCI BAR space, Big Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018WriteBE32
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    int               offset,
    int               numItems,
    unsigned int      *pData
)
```

DESCRIPTION

This function writes the specified number of items to the PCI BAR space by using 32-bit accesses.

The values are written in Big Endian Mode, that means on Intel x86 architectures the multibyte data will be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (32-bit) to write.

pData

This argument is a pointer to an unsigned short buffer with the data items to write. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned int      data;

data      = 0x12345678;
offset    = 0xF8;
/*
** Write Test data into 32bit Scratchpad Register
*/
result = tdrv018WriteBE32( hdl, TDRV018_RES_MEM_3,
                          offset, 1, &data );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVALID	The specified access range exceeds PCI BAR limits

2.6.10 tdrv018WriteLE32

NAME

tdrv018WriteLE32 – write 32-bit values to the PCI BAR space, Little Endian Mode

SYNOPSIS

```
TDRV018_STATUS tdrv018WriteLE32
(
    TDRV018_HANDLE    hdl,
    int                pciResource,
    int                offset,
    int                numItems,
    unsigned int       *pData
)
```

DESCRIPTION

This function writes the specified number of items to the PCI BAR space by using 32-bit accesses.

The values are written in Big Endian Mode, that means on Intel x86 architectures the multibyte data will not be byte-swapped.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

offset

This argument specifies the start offset (byte address) within the PCI BAR space.

numItems

This argument specifies the number of items (32-bit) to write.

pData

This argument is a pointer to an unsigned short buffer with the data items to write. The allocated space must be large enough to hold the specified amount of data.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
int               offset;
unsigned int      data;

data      = 0x12345678;
offset    = 0xF8;
/* Write Test data into 32bit Scratchpad Register */
result = tdrv018WriteLE32( hdl, TDRV018_RES_MEM_3, offset, 1, &data );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_ACCESS	Specified PCI resource not available or reserved
TDRV018_ERR_INVALID	The specified access range exceeds PCI BAR limits

2.7 Resource Mapping Functions

2.7.1 tdrv018PciResourceMap

NAME

tdrv018PciResourceMap – map a PCI resource directly into the process context

SYNOPSIS

```
TDRV018_STATUS tdrv018PciResourceMap
(
    TDRV018_HANDLE    hdl,
    int               pciResource,
    unsigned char     **pPtr,
    unsigned int      *pSize
)
```

DESCRIPTION

This function maps the specified PCI resource of the hardware module directly into the process context. The retrieved pointer can be used for direct non-cached register access.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pciResource

This parameter specifies the desired PCI Memory resource to be used for this access. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

The Base Address Register usage is programmable and can be changed by modifying the PCI Configuration EEPROM. Therefore the following table is just an example how the PCI Base Address Registers could be used.

PCI Base Address Register	PCI Address-Type	TDRV018 Resource
0	<i>reserved</i>	TDRV018_RES_MEM_1
1	<i>reserved</i>	TDRV018_RES_MEM_2
2	MEM	TDRV018_RES_MEM_3
3	MEM (<i>not used</i>)	TDRV018_RES_MEM_4
4	MEM (<i>not used</i>)	TDRV018_RES_MEM_5
5	MEM (<i>not used</i>)	TDRV018_RES_MEM_6

pPtr

This argument is a pointer to an unsigned char pointer that receives the start address of the mapped PCI resource.

pSize

This argument returns the size of the mapped PCI resource in bytes.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned char     *pReg;
unsigned int      size;

/*
** map first memory PCI resource
*/
result = tdrv018PciResourceMap( hdl, TDRV018_RES_MEM_3, &pReg, &size );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_NOMEM	Unable to allocate memory

2.7.2 tdrv018PciResourceUnmap

NAME

tdrv018PciResourceUnmap – unmap a previously mapped PCI resource

SYNOPSIS

```
TDRV018_STATUS tdrv018PciResourceUnmap  
(  
    TDRV018_HANDLE    hdl,  
    unsigned char     *pPtr  
)
```

DESCRIPTION

This function unmaps a previously mapped PCI resource, freeing the system resources used for this mapping.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pPtr

This argument is a pointer to an unsigned char pointer that represents the start address of the previously mapped PCI resource. This pointer must have been received from the corresponding mapping function.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned char      *pReg;

/*
** unmap a previously mapped PCI resource
*/
result = tdrv018PciResourceUnmap( hdl, pReg );

if (result != TDRV018_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified device handle is invalid
TDRV018_ERR_INVAL	Invalid pointer specified

2.8 Interrupt Functions

2.8.1 tdrv018InterruptWait

NAME

tdrv018InterruptWait – Wait for incoming Local Interrupt Source

SYNOPSIS

```
TDRV018_STATUS tdrv018InterruptWait
(
    TDRV018_HANDLE    hdl,
    unsigned int      interruptMask,
    unsigned int      *pInterruptOccurred,
    int               timeout
)
```

DESCRIPTION

This function enables the specified local interrupt sources, and waits for these Local Interrupt Sources to arrive. After an interrupt has arrived, the corresponding occurred local interrupt source is disabled. Multiple functions may wait for the same interrupt source to occur.

The delay between an incoming interrupt and the return of the described function is system-dependent, and is most likely several microseconds.

For high interrupt load, a customized device driver should be used which serves the module-specific functionality directly on interrupt level.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

interruptMask

This parameter specifies specific interrupt bits to wait for. The function returns if at least one of the specified interrupt sources is detected. The following values are possible:

Value	Description
TDRV018_INTSTAT_LBUSR	User FPGA Interrupt
TDRV018_INTSTAT_LBERR	Local Bus Error Interrupt

pInterruptOccurred

If at least one of the specified interrupt sources occurs, the value is returned through this pointer.

timeout

This value specifies the timeout in milliseconds the function will wait for the interrupt to arrive. The granularity depends on the operating system. To wait indefinitely, specify -1 as timeout parameter.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE    hdl;
TDRV018_STATUS    result;
unsigned int      interruptMask;
unsigned int      interruptOccurred;

/*
** Wait at least 5 seconds for incoming Local Bus User Interrupt
*/
interruptMask = TDRV018_INTSTAT_LBUSR;
result = tdrv018InterruptWait(    hdl,
                                interruptMask,
                                &interruptOccurred,
                                5000 );

if (result == TDRV018_OK)
{
    /* Interrupt arrived. */
    /* Now acknowledge interrupt source in FPGA logic */
    /* to clear the Local Interrupt Source. */
    /* Use tdrv018Read and tdrv018Write functions for */
    /* register access. */
} else {
    /* handle error */
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_TIMEOUT	The specified timeout occurred.

2.8.2 tdrv018InterruptRegisterCallbackThread

NAME

tdrv018InterruptRegisterCallbackThread – Register a User Callback Function for Interrupt Handling

SYNOPSIS

```
TDRV018_STATUS tdrv018InterruptRegisterCallbackThread
(
    TDRV018_HANDLE    hdl,
    int               threadPriority,
    int               stackSize,
    unsigned int      interruptMask,
    FUNCINTCALLBACK  callbackFunction,
    void              *funcparam,
    TDRV018_HANDLE    *pCallbackHandle
)
```

DESCRIPTION

This function registers a user callback function which is executed after detection of the specified interrupt source. Multiple callback functions can be registered to each interrupt source. The callback function is executed in a high-priority thread context, so using TDRV018 device driver functions is allowed. The callback function should be kept as short as possible. The specified callback function is executed with the occurred interrupt bits and the specified function parameter as function arguments. Additionally, a status value is passed to the callback function for proper error handling.

The delay between an incoming interrupt and the execution of the callback function is system-dependent, and is most likely several microseconds.

For high interrupt load, a customized device driver should be used which serves the module-specific functionality directly on interrupt level.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

threadPriority

This parameter specifies the priority to be used for the callback thread. Possible values are:

Value	Description
TDRV018_PRIORITY_NORMAL	Normal Thread Priority
TDRV018_PRIORITY_HIGH	High Thread Priority
TDRV018_PRIORITY_LOW	Low Thread Priority

Other values might be possible, depending on the used operating system.

threadSize

This parameter specifies the stack size to be used for the callback thread. The value is specified in bytes.

interruptMask

This parameter specifies specific interrupt bits to handle. The callback function is executed if at least one of the specified interrupt sources occurred. The following values are possible:

Value	Description
TDRV018_INTSTAT_LBUSR	User FPGA Interrupt
TDRV018_INTSTAT_LBERR	Local Bus Error Interrupt

callbackFunction

This parameter is a function pointer to the user callback function. The callback function pointer is defined as follows:

```
typedef void(*FUNCINTCALLBACK)( TDRV018_HANDLE  hdl,
                                unsigned int      interruptOccurred,
                                void              *param,
                                TDRV018_STATUS  status );
```

hdl

This parameter specifies a device handle which can be used for hardware access or other API functions by the callback function.

interruptOccurred

This parameter is a 32bit value reflecting the occurred interrupts. Possible values correspond to the *interruptMask*.

param

This parameter is the user-specified *funcparam* value (see below) which has been specified on callback registration. This value can be used to pass a pointer to a specific control structure, to supply the callback function with specific information.

status

This parameter hands over interrupt callback status information. The callback function needs to check this parameter. If the specified interrupt source has occurred properly, and no errors were detected, this parameter is TDRV018_OK. If this parameter differs from TDRV018_OK, an internal error has been detected and the callback handling is stopped. The callback function must implement an appropriate error handling.

funcparam

This value specifies a user parameter, which will be handed over to the callback function on execution. This parameter can be used to pass a pointer to a specific control structure used by the callback function.

pCallbackHandle

This value specifies a pointer to a handle, where the callback handle will be returned. This callback handle must be used to unregister a callback function.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE      hdl;
TDRV018_STATUS      result;
unsigned int         interruptMask;
USER_DATA_AREA      userDataArea[2];
TDRV018_HANDLE      callbackHandle[2];

/* forward declaration of callback functions */
void callback_INPUT(  TDRV018_HANDLE      hdl,
                     unsigned int         interruptOccurred,
                     void                 *param,
                     TDRV018_STATUS      status );

void callback_INPUTdirect(  TDRV018_HANDLE      hdl,
                           unsigned int         interruptOccurred,
                           void                 *param,
                           TDRV018_STATUS      status );

...

/*
** Register callback function for INPUT (LBUSR)
** Use a "normal" priority, and 64KB stack.
*/
interruptMask = TDRV018_INTSTAT_LBUSR;
result = tdrv018InterruptRegisterCallbackThread( hdl,
                                                  TDRV018_PRIORITY_NORMAL,
                                                  0x10000,
                                                  interruptMask,
                                                  callback_INPUT,
                                                  &userDataArea[0],
                                                  &callbackHandle[0] );

...
```

```
...
if (result != TDRV018_OK)
{
    /* handle error */
}

/*
** Map Device Register Space for direct access
*/
result = tdrv018PciResourceMap( hdl,
                                TDRV018_RES_MEM_3,
                                &userDataArea[1].pRegSpace,
                                &userDataArea[1].resSize );

if (result != TDRV018_OK)
{
    /* handle error */
}

...

/*
** Register callback function for INPUT (LBUSR), using direct access
** Use a "normal" priority, and 64KB stack.
*/
interruptMask = TDRV018_INTSTAT_LBUSR;
result = tdrv018InterruptRegisterCallbackThread( hdl,
                                                  TDRV018_PRIORITY_NORMAL,
                                                  0x10000,
                                                  interruptMask,
                                                  callback_INPUTdirect,
                                                  &userDataArea[1],
                                                  &callbackHandle[1] );

/*
** Initialize the Input Interrupt functionality, using register accesses.
** Refer to the FPGA Example documentation for register description.
*/
...
```

```
...
/*
** Callback Function, using API Functions for Register Access
*/
void callback_INPUT(    TDRV018_HANDLE    hdl,
                       unsigned int      interruptOccurred,
                       void              *param,
                       TDRV018_STATUS    status )
{
    TDRV018_STATUS    result;
    USER_DATA_AREA   *pUsrData = (USER_DATA_AREA*)param;
    unsigned int      intstat;

    if (status != TDRV018_OK)
    {
        /* handle error status */
    }
    /* read Input Interrupt Status Register */
    result = tdrv018WriteLE32(    hdl,
                                  TDRV018_RES_MEM_3,
                                  0x28,
                                  1,
                                  &intstat );

    if (intstat != 0)
    {
        printf("[Input Interrupt]\n");

        /* Acknowledge INPUT interrupt source by writing to
        ** "Interrupt Status Register" */
        result = tdrv018WriteLE32(    hdl,
                                        TDRV018_RES_MEM_3,
                                        0x28,
                                        1,
                                        &intstat );
    }
    ...

    /* handle errors */
    return;
}
...
```

```
...

/*
** Alternative Callback Function, using direct Register Access
*/
void callback_INPUTdirect(  TDRV018_HANDLE    hdl,
                           unsigned int      interruptOccurred,
                           void              *param,
                           TDRV018_STATUS    status )
{
    TDRV018_STATUS    result;
    USER_DATA_AREA  *pUserData = (USER_DATA_AREA*)param;
    unsigned int      *pStatusReg;
    unsigned int      instat;

    if (status != TDRV018_OK)
    {
        /* handle error status */
    }

    /* calculate 32bit pointer to "Input Interrupt Status Register" */
    pStatusReg = (unsigned int*)(pUserData->pRegSpace + 0x28);

    /* depending on the system architecture, the 32bit value must be
    ** adapted to the endianness (little or big endian).
    ** Use the provided API functions to handle this. */
    intstat = endian_le32(*pStatusReg);
    if (intstat != 0)
    {
        /* Acknowledge INPUT interrupt source. */
        *pStatusReg = endian_le32(intstat);

        /* handle the input interrupt */
    }

    return;
}
```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified TDRV018_HANDLE is invalid.
TDRV018_ERR_INVALID_PARAMETER	Function or callback handle pointer is NULL.

Other returned error codes are system error conditions.

2.8.3 tdrv018InterruptUnregisterCallback

NAME

tdrv018InterruptUnregisterCallback – Unregister a User Callback Function

SYNOPSIS

```
TDRV018_STATUS tdrv018InterruptUnregisterCallback  
(  
    TDRV018_HANDLE    hdl  
)
```

DESCRIPTION

This function unregisters a previously registered user callback function.

PARAMETERS

hdl

This value specifies the callback handle retrieved by a call to the corresponding register-function.

EXAMPLE

```
#include "tdrv018api.h"  
  
TDRV018_HANDLE    callbackHdl;  
TDRV018_STATUS    result;  
  
/*  
**  Unregister a callback function  
*/  
result = tdrv018InterruptUnregisterCallback( callbackHdl );  
if (result == TDRV009_OK)  
{  
    /* OK */  
} else {  
    /* handle error */  
}
```


RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified callback handle is invalid.

Other returned error codes are system error conditions.

2.8.4 tdrv018InterruptConfig

NAME

tdrv018InterruptConfig – Configure the Interrupt handling method for User-FPGA implementations

SYNOPSIS

```
TDRV018_STATUS tdrv018InterruptConfig
(
    TDRV018_HANDLE    hdl,
    int               ControlType,
    int               ReadPciResource,
    int               ReadAccessWidth,
    unsigned int      ReadOffset,
    unsigned int      ReadMask,
    int               WritePciResource,
    int               WriteAccessWidth,
    unsigned int      WriteOffset,
    unsigned int      WriteMask,
    unsigned int      WriteValue
);
```

DESCRIPTION

This function configures the interrupt handling method for User-FPGA specific implementations. Interrupt handling must be implemented on driver-level, so the driver must be configured properly to acknowledge an interrupt of the user-specific FPGA implementation. This function is only supported by User-FPGA devices.

For User-FPGA devices, make sure to configure the interrupt handling before the User-FPGA implementation raises interrupts.

PARAMETERS

hdl

This value specifies the callback handle retrieved by a call to the corresponding register-function.

IntAckMethod

This value specifies the interrupt acknowledgement method. Following values are possible:

Value	Description
TDRV018_INTACK_READ	Interrupt is cleared upon reading a status register.
TDRV018_INTACK_READCLEAR	Interrupt is cleared by writing the read register bits into the same register, using the same access width as for the read access.
TDRV018_INTACK_READWRITE	Interrupt is cleared upon writing a static value to a specific register.
TDRV018_INTACK_READWRITEMASK	Interrupt is cleared upon writing a static value to a specific register using a bit-mask, leaving specified original register bits unchanged.

ReadPciResource

This parameter specifies the desired PCI Memory resource to be used for reading the interrupt status. In general, a PCI target supports up to six base address registers. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

ReadAccessWidth

This parameter specifies the desired access width for reading the interrupt status. The driver always uses little-endian accesses. Following values are possible:

Value	Description
TDRV018_ACCESSWIDTH_8	A BYTE (8bit) register access is used.
TDRV018_ACCESSWIDTH_16	A WORD (16bit) register access is used.
TDRV018_ACCESSWIDTH_32	A DWORD (32bit) register access is used.

ReadOffset

This argument specifies the register offset within the PCI BAR space used for reading the interrupt status.

ReadMask

This argument specifies the bit-mask used for interrupt detection. This argument can be used to mask-out static register bits for proper support of PCI interrupt sharing.

WritePciResource

This parameter specifies the desired PCI Memory resource to be used for writing a static value. In general, a PCI target supports up to six base address registers. This parameter is not used for IntAckMethod READ and READCLEAR. Following values are possible:

Value	Description
TDRV018_RES_MEM_1	First found PCI Memory area.
TDRV018_RES_MEM_2	Second found PCI Memory area.
TDRV018_RES_MEM_3	Third found PCI Memory area.
TDRV018_RES_MEM_4	Fourth found PCI Memory area.
TDRV018_RES_MEM_5	Fifth found PCI Memory area.
TDRV018_RES_MEM_6	Sixth found PCI Memory area.

WriteAccessWidth

This parameter specifies the desired access width for writing the static value. The driver always uses little-endian accesses. This parameter is not used for IntAckMethod READ and READCLEAR. Following values are possible:

Value	Description
TDRV018_ACCESSWIDTH_8	A BYTE (8bit) register access is used.
TDRV018_ACCESSWIDTH_16	A WORD (16bit) register access is used.
TDRV018_ACCESSWIDTH_32	A DWORD (32bit) register access is used.

WriteOffset

This argument specifies the register offset within the PCI BAR space used for writing the static value. This parameter is not used for IntAckMethod READ and READCLEAR.

WriteMask

This argument specifies the bit-mask used for write access. This argument can be used to mask-out static register bits, changing only the desired ones. Specifying 0x00000000 is not valid. This parameter is not used for IntAckMethod READ and READCLEAR.

WriteValue

This argument specifies the static value to be used for writing. This parameter is not used for IntAckMethod READ and READCLEAR.

EXAMPLE

```
#include "tdrv018api.h"

TDRV018_HANDLE          hdl;
TDRV018_STATUS          result;

/*
** Example 1:
** Configure the Interrupt Handler to use READCLEAR method
** - InterruptStatus Register in first PCI MemRes, at Offset 0x20
** - Use 32bit accesses
*/
result = tdrv018InterruptConfig( hdl,
                                TDRV018_INTACK_READCLEAR,
                                TDRV018_RES_MEM_1,          // ReadPciResource
                                TDRV018_ACCESSWIDTH_32,     // ReadAccessWidth
                                0x20,                       // ReadOffset
                                0xFFFFFFFF,                 // check all register-bits
                                0, 0, 0, 0, 0               // do not use write-
                                                                // parameters
                                );
if (result == TDRV018_OK)
{
    / *OK */
} else {
    /* handle error */
}

...
```

```

/*
** Example 2:
** Configure the Interrupt Handler to use READWRITE method
** - InterruptStatus Register at PCI Memory Resource 1, Offset 0x20
** - Use 32bit accesses, check all register-bits
** - disable the Interrupt by writing 0x00000000 to PCI Memory Resource 1,
**   Offset 0x24
*/
result = tdrv018InterruptConfig( hdl,
                                TDRV018_INTACK_READWRITE,
                                TDRV018_RES_MEM_1,           // ReadPciResource
                                TDRV018_ACCESSWIDTH_32,      // ReadAccessWidth
                                0x20,                        // ReadOffset
                                0xFFFFFFFF,                  // ReadMask
                                TDRV018_RES_MEM_1,           // WritePciResource
                                TDRV018_ACCESSWIDTH_32,      // WriteAccessWidth
                                0x24,                        // WriteOffset
                                0xFFFFFFFF,                  // WriteMask
                                0x00000000                   // WriteValue
                                );
if (result == TDRV018_OK)
{
    / *OK */
} else {
    /* handle error */
}

```

RETURNS

On success, TDRV018_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

Error Code	Description
TDRV018_ERR_INVALID_HANDLE	The specified handle is invalid.
TDRV018_ERR_INVALID	The specified flags are invalid.
TDRV018_ERR_NOSYS	This function is not supported by the device.

2.9 Endian Conversion Functions

The following conversion functions can be used to develop endian-neutral software, especially for direct access to mapped PCI resources.

2.9.1 endian_be16

NAME

endian_be16 – big-endian conversion function

SYNOPSIS

```
unsigned short endian_be16
(
    unsigned short    u16value
)
```

DESCRIPTION

This function converts a short integer value (16-bit) from the native CPU endian order to big-endian order. That means on Intel x86 architectures the value will be byte-swapped, as opposed to PowerPC architectures.

PARAMETERS

u16value

This argument specifies the data to convert

EXAMPLE

```
#include "tdrv018api.h"

unsigned short *pRawData, bigEndianData;

/* setup pRawData pointer to the correct location first */

bigEndianData = endian_be16(*pRawData);
```

RETURN VALUE

This function returns the passed value in the big-endian order.

2.9.2 endian_le16

NAME

endian_le16 – little-endian conversion function

SYNOPSIS

```
unsigned short endian_le16
(
    unsigned short    u16value
)
```

DESCRIPTION

This function converts a short integer value (16-bit) from the native CPU endian order to little-endian order. That means on PowerPC architectures the value will be byte-swapped, as opposed to Intel x86 architectures.

PARAMETERS

u16value

This argument specifies the data to convert

EXAMPLE

```
#include "tdrv018api.h"

unsigned short *pRawData, littleEndianData;

/* setup pRawData pointer to the correct location first */

littleEndianData = endian_le16(*pRawData);
```

RETURN VALUE

This function returns the passed value in the little-endian order.

2.9.3 endian_be32

NAME

endian_be32 – big-endian conversion function

SYNOPSIS

```
unsigned int endian_be32
(
    unsigned short    u32value
)
```

DESCRIPTION

This function converts an integer value (32-bit) from the native CPU endian order to big-endian order. That means on Intel x86 architectures the value will be byte-swapped, as opposed to PowerPC architectures.

PARAMETERS

u32value

This argument specifies the data to convert

EXAMPLE

```
#include "tdrv018api.h"

unsigned short *pRawData, bigEndianData;

/* setup pRawData pointer to the correct location first */

bigEndianData = endian_be32(*pRawData);
```

RETURN VALUE

This function returns the passed value in the big-endian order.

2.9.4 endian_le32

NAME

endian_le32 – little-endian conversion function

SYNOPSIS

```
unsigned short endian_le32
(
    unsigned short    u32value
)
```

DESCRIPTION

This function converts an integer value (32-bit) from the native CPU endian order to little-endian order. That means on PowerPC architectures the value will be byte-swapped, as opposed to Intel x86 architectures.

PARAMETERS

u32value

This argument specifies the data to convert

EXAMPLE

```
#include "tdrv018api.h"

unsigned short *pRawData, littleEndianData;

/* setup pRawData pointer to the correct location first */

littleEndianData = endian_le32(*pRawData);
```

RETURN VALUE

This function returns the passed value in the little-endian order.

3 Debugging and Diagnostic

The TDRV018 device driver provides functions and debug statements to display versatile information of the driver installation and status on the debugging console.

If the VxBus driver is used, the TDRV018 show routine is included in the driver by default and can be called from the VxWorks shell. If this function is not needed or program space is rare the function can be removed from the code by un-defining the macro INCLUDE_TDRV018_SHOW in tdrv018drv.c

The tdrv018Show function (only if VxBus is used) displays detailed information about probed modules, assignment of devices respective device names to probed TDRV018 modules and device statistics.

If TDRV018 modules were probed but no devices were created it may be helpful to enable debugging code inside the driver code by defining the macro TDRV018_DEBUG in tdrv018drv.c.

In contrast to VxBus TDRV018 devices, legacy TDRV018 devices must be created “manually”. This will be done with the first call to the tdrv018Open API function.

```
-> tdrv018Show
Probed Modules:
  [0] TXMC633-BCC: Bus=6, Dev=0, DevId=0x9279, VenId=0x1498, Init=OK,
vxDev=0xffff800000004910
  [1] TXMC633-FPGA: Bus=7, Dev=0, DevId=0x9279, VenId=0x1498, Init=OK,
vxDev=0xffff800000004d70
  [2] TPMC634: Bus=10, Dev=2, DevId=0x027a, VenId=0x1498, Init=OK, vxDev=0xffff800000006580

Associated Devices:
  [0] TXMC633-BCC: /tdrv018/0
  [1] TXMC633-FPGA: /tdrv018/1
  [2] TPMC634: /tdrv018/2

Device Statistics:
/tdrv018/0:
  open count          = 0
  job count           = 0
  interrupt count     = 0

  Available PCI Resources:
  [0] : reserved
  [1] : reserved

/tdrv018/1:
  open count          = 0
  job count           = 0
  interrupt count     = 0

  Available PCI Resources:
  [0] : address = 0xffff800020200000 size=0x200000
  [1] : address = 0xffff800020400000 size=0x200000
  [2] : address = 0xffff800020600000 size=0x800000

/tdrv018/2:
```

```
open count          = 0
job count           = 0
interrupt count     = 0
```

```
Available PCI Resources:
```

```
[0] : reserved
[1] : reserved
[2] : address = 0xffff800020043000 size=0x40000
```

```
value = 3 = 0x3
```