





TPIM001 PIM I/O Module with 50 pin Connector





Application Information

The TPIM001 is a standard single-width PIM I/O module to be used with any PIM carrier. It offers easy access to the PMC back I/O lines of PMC carrier with back I/O.

The TPIM001 distributes the lower 50 I/O lines of the PMC to a standard 50 pin SCSI-2 type connector located in the EMI front panel.

The operating temperature range is -40°C to +85°C.

Technical Information

- O Standard single-width PIM I/O Module
- O Board size: 69 mm x 74 mm
- I/O lines 1 to 50 are routed to a HD50 SCSI-2 type connector in the front panel
- O EMI Front Panel
- O Operating Temperature: -40°C to +85°C

Order Information

RoHS Compliant

TPIM001-10R PIM I/O Module, HD50 connector

For the availability of non-RoHS compliant (leaded solder) products please contact TEWS.

Documentation

TPIM001-DOC User Manual



Ehlbeek 15a 30938 Burgwedel fon 05139-9980-0 fax 05139-9980-49

www.powerbridge.de info@powerbridge.de

TEWS TECHNOLOGIES GmbH keeps the right to change technical specification without further notice. All trademarks mentioned are property of their respective owners.

Issue 1.0.1 2017-08-31

Am Bahnhof 7 25469 Halstenbek, Germany Phone: +49 (0) 4101 4058 0 Fax: +49 (0) 4101 4058 19

e-mail: info@tews.com www.tews.com