

# cPS-H325/AC, H325/48

## PICMG® 2.11 47-pin Hot-Swap Redundant 3U CompactPCI® 8HP 250 W Power Module

### Features

- PICMG® 2.11 CompactPCI® Power Interface compliant
- 3U CompactPCI® 8HP form factor
- PICMG® 2.11 47-pin CompactPCI® in-rack power module interface
- 250 W DC output
- Active PFC (Power Factor Correction) meets IEC1000-3-2 Harmonic Correction
- Internal OR-ing Diodes for N + 1 redundancy
- Hot swappable
- Active current sharing
- EMI meets EN 55022 & FCC Class A
- Supports remote ON/OFF
- Supports power failure signal & degradation signal



### Specifications

Model Name: cPS-H325/AC  
 PICMG® Standards: PICMG® 2.11 CompactPCI®  
 Form Factor: 3U cPCI (100 x 160mm), 2-slot (8HP) wide  
 Input Voltage: 90-264 ± 10% VAC  
 Input Frequency: 47-63 ± 5% Hz  
 Input Current: 2.8 A @ 115 VAC  
 1.4 A @ 230 VAC  
 Inrush Current: <30 A @ 230 VAC

Model Name: cPS-H325/48  
 PICMG® Standards: Power Interface compliant  
 Form Factor: 3U cPCI (100 x 160mm), 2-slot (8HP) wide  
 Input Voltage: 36-72 VDC  
 Input Frequency: DC  
 Input Current: typ. 20A @ 48 VDC  
 Inrush Current: N/A

**Power Factor (PFC, only for AC)**  
 Correction Typical 0.95-0.97  
 Meets Harmonic Correction IEC1000-3-2

#### Output Voltage/Current

5V: Typ. 25.0A, Max. 33.0A  
 3.3V: Typ. 18.0A, Max. 33.0A  
 +12V: Typ. 5.0A, Max. 6A  
 -12V: Typ. 0.5A, Max. 1.5A

Max. load is the continuous operating load of each rail individually. The max. load of each rail cannot be drawn from all outputs simultaneously.

#### Output Voltage

0.5 A @ +5 V  
 Minimum Load

#### Output Wattage

Typical 250W continuous  
 Line Regulation: Typical 0.1%  
 Load Regulation: Typical ± 1-2%  
 Ripple: 50 mV @ +5 V and 3.3 V outputs  
 120 mV @ +12 V and -12 V outputs  
 Hold-up Time: 5 ms after power fail signal  
 Efficiency: Typical 78-79%

#### Output Voltage Sense

Available at 5V, 3.3V, and +12V outputs and current sharing  
 N+1 Redundancy: Equipped with internal OR-ing diodes at all outputs for N+1 redundancy operation  
 Remote ON/OFF: Available at [INH#] & [EN#]

#### Power Failure Signal

Available at [FAL#] pin

#### Power Degradation Signal

Available at [DEG#] pin

powerBridge  
 Computer

Ehlbeek 15a  
 30938 Burgwedel  
 fon 05139-9980-0  
 fax 05139-9980-49

www.powerbridge.de  
 info@powerbridge.de

## Specifications

### Protections

Over Temperature Protection (OTP): +70°C  
Over Current Protection (OCP): Installed at each rail  
Over Load Protection (OLP): Typical 120% max. load, fully protected against output overload or short circuit.  
Over Voltage Protection (OVP): Built-in at all outputs

### Status LED

<Green LED> [POWER] means valid input voltage  
<Amber LED> [FAULT] means a critical fault  
Earth Leakage: <0.5 mA @ 230 VAC <0.5 mA @ 48 VDC <0.5 mA @ 24 VDC

### Operating Temperature

-40 °C to +70 °C at full load with at least 600LFM air flow Derates linearly to 60% at +70°C for H325/24 (A warm-up time 3 minutes is required after cold start at temperatures from -40 °C to +0°C.)

### Storage Temperature

-45°C to +85°C

### Humidity

5% to 95% non-condensing

### Shock

15 G peak-to-peak, 11 ms duration, non-operation

### Vibration

Operation: 1.88 Grms, 5-500 Hz, each axis  
Cooling Requirement: Min. 20 CFM is required for typical full power rating

### Certifications

IEC950, EN 55022, FCC Class A, IEC60950 Class I

## Ordering Information

- **cPS-H325/AC**  
PICMG® 2.11 47-pin hot-swap redundant 3U CompactPCI®  
8HP 250 W power module with universal AC Input
- **cPS-H325/48**  
PICMG® 2.11 47-pin hot-swap redundant 3U CompactPCI®  
8HP 250 W power module with 36-72VDC Input

