



powerBridge
Computer

Ehlbeek 15a
30938 Burgwedel
fon 05139-9980-0 www.powerbridge.de
fax 05139-9980-49 info@powerbridge.de



XRS 3U-IP SERIES

EXTREME RUGGED SERVERS
IP54 RATED

XRS 3U-IP Series

EXTREME RUGGED SERVERS




XRS is a line of extreme rugged servers combining superior robustness with high performance computing technology, designed for applications that require a MIL-grade qualified equipment, suitable for operations in very critical environment.

XRS 3U-IP features a powerful single or dual socket Intel® Xeon® Platform suitable for the most intense workloads and supporting a generous number of PCIe 3.0 lanes. The integrated IPMI services support monitoring, control, and management functions sending alarm notifications in case of critical events.

XRS 3U-IP Extreme Rugged Server has an IP54 protection rate and features a 3U milled aluminium chassis designed to provide for superior resistance. The unit is equipped with MIL grade connectors for I/O ports and for power input. XRS can host up to six full size PCIe boards including GPU, FPGA modules and any other powerful PCI Express board. The front panel includes VGA, IPMI LAN, USB 3.0 and USB 2.0 and a removable battery holder. Two 3.5" drive bays can host up to six removable SSDs.

XRS 3U-IP Extreme Rugged Servers are qualified according to MIL-STD-810G for temperature, shocks and vibrations, and conforms to MIL-STD-461 for EMI/EMC. Specific customer's configurations can be delivered fully integrated and tested.

Product Features

-  High Performance Dual Xeon® Architecture
-  IPMI Based Management
-  Extreme Rugged Aluminum Chassis
-  IP54 Protection Grade
-  D38999 Circular Connectors and Conformal Coating
-  MIL Grade Qualifications

Technical Specifications

System

Processor Module	2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support up to 140W TDP
Memory	Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; DDR4-2933MHz, in 8 DIMM slots
Chipset	Intel® C621
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Serial	1x COM Port (1 header)
USB	4x USB 2.0 ports (2 rear + 2 via headers) 3x USB 3.2 Gen1 ports (2 via headers + 1 Type A)
Storage	10 SATA3 (6Gbps) port
TPM	TPM header
I/O Expansion	2x PCIe 3.0 x16, 3x PCIe 3.0 x8, 1x PCIe 3.0 x4 (in x8 slot) M.2 Interface: 1 SATA/PCIe 3.0 x4, Form Factor: 2260, 2280; Key: M-Key
Software	Windows® 10 IoT Enterprise 2016, Windows® Server 2016, Linux, Vmware
IPMI	IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications
Remote Monitoring	Monitoring, control and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, raid health, and memory health)

Power Section

Power Input	AC or DC input single power supply with EMC Filter and MIL D38999 connector
-------------	---

Mechanical Features

Dimensions (W x D x H)	Width 483mm Depth 530mm overall Height 132mm - 3U rack
Material	Aluminum with surface passivation treatment
Weight	19,5 Kg (depending on configuration)
Color	Black / other on request
Mounting	3U 19" rackmount chassis with bridge handles Optional telescopic slides
Front Panel	LEDs for Power ON and SYS Fail Power On Switch Protected by the front panel: 1x VGA, 2x USB 3.0, 2x USB 2.0, IPMI LAN, Removable Battery
Drive Bay	2x 3.5" drive bays hosting up to 6x 2.5" SSD
Rear Panel	Power Input connector, D38999 MIL type connectors

Environmental Features

Operating Temperature	Standard: 0°C / +50°C Extended: -20°C / +60°C (depending on configuration)
Storage Temperature	-40°C / +71°C
Humidity	8% to 95% non-condensed (depending on the configuration)
Fungus	Conformal coating on request
IP Protection	IP54
Shock	Logistical 40G/11ms (3 shocks per axis and direction) Tactical 35G/20ms + 80G/2ms half sine (1 shock per axis and direction)
Vibrations	MIL-STD-810G, Method 514.7
Electromagnetic Compatibility	According to MIL-STD-461E





GOMA ELETTRONICA SpA

Strada Antica di Collegno, 225
10146 Torino - Italia

Tel: +39 011 7725024

Fax: +39 011 712298

www.gomarugged.com

All trademarks are the property of their respective owners
GOMA ELETTRONICA SpA · XRS3UIP0122

Designed by GOMA ELETTRONICA SpA



KEEP IN TOUCH

