

MTCA.4™  
MicroTCA™  
AdvancedMC™

Catalogue 2024



powerBridge  
Computer

# Index

|  |    |
|--|----|
| About us   | 1  |
| MicroTCA and MTCA.4                              | 3  |
| MTCA.4 Starter Kits                              | 4  |
| MicroTCA Chassis                                 | 5  |
| MTCA.4 Chassis                                   | 6  |
| MicroTCA Carrier Hubs                            | 7  |
| AdvancedMC CPU-Modules, x86 and ARM              | 8  |
| AdvancedMC I/O-Modules – Field Bus               | 9  |
| AdvancedMC I/O-Modules – Carrier Board and FPGA  | 10 |
| AdvancedMC I/O-Modules – FPGA/ADC/DAQ            | 11 |
| AdvancedMC I/O-Modules – DSP/FPGA                | 14 |
| AdvancedMC I/O-Modules – Telecom and JTAG        | 16 |
| AdvancedMC I/O-Modules – Storage and Development | 17 |
| AdvancedMC I/O-Modules – Misc.                   | 18 |
| MicroTCA – Power Modules                         | 19 |
| MicroTCA – Software                              | 20 |
| AdvancedMC Specification                         | 21 |



powerBridge Computer supplies computer systems and computer boards from leading manufacturers since 1993. We design and integrate industrial computers, communication systems and boards according to our customers requirements.

You benefit from our experience in hundreds of industrial applications in automation, research, medical technology, telecommunications, transportation, aero space and defense engineering for more than 20 years. We offer system solutions which comply perfectly with your requirements for performance, reliability, stability, costs and product durability.

Our product range covers boards, chassis, systems and HA solutions based on industrial standards like AdvancedTCA, CompactPCI, VMEbus, VPX, MicroTCA, AMC, FMC, PMC and IndustryPack mezzanine modules. In addition to system integration and OEM solutions we offer development systems, drivers, protocols and protocol integration. We support our offer with Windows, Linux and Real-Time operating systems.

# Our Effort for Your Success



## Design Support

Consulting

Software Expertise

Technical Training

Manufacturer Independent Support

Product Adaptation

Product Hardening

Customization Product Development

Driver Adaptation

## Production Support

Integration Service

Prototype Construction

Series Production

Quality Management

Test and Certification

Just in Time Shipment

Customer Stock

Security Stock

## After Sales Support

Online Services

Technical Support

Update Service

Extended Warranty Service

Product Life Cycle Management

First Class Repair Service



# MicroTCA & MTCA.4

## That's MicroTCA!

MicroTCA defines backplane-based computer systems based on Advanced MC (AMC) modules. MicroTCA systems are used in industry, research, medical technology, vehicle engineering, defence engineering, telecommunications and network engineering.

## Highly Scalable Systems

The MicroTCA specification defines highly scalable systems – from simple low-cost systems to high-available carrier grade computer architectures. Depending on its configuration, one chassis can hold up to 12 AMC modules. Several chassis can be easily linked together. Modules with any function can be used in each slot. It goes without saying that any operating system and processor architecture can be used. In addition to the AMC modules, a MicroTCA system has at least one MicroTCA carrier hub (MCH) as well as at least one power module (PM). Originally intended only for telecommunication applications, MicroTCA systems have now been introduced in many areas.

AMC modules communicate with each other by way of switched fabrics. Ethernet (1GbE, 10GbE, 40GbE), PCI Express, RapidIO, SATA and SAS are defined as possible protocols. AMC modules are available in various front panel widths and also optionally in double board size.

## MicroTCA Carrier Hub

The MCH defines the connections, monitors the whole system and generates the system clocks. It also monitors and manages the AMC modules, up to 4 power modules (PM) and 2 cooling units (CU). It provides the required switching functionality.

The MCH has the form of an AMC module, but consists of several PCBs and has a dedicated system slot. For fail-safe systems, two MCHs can be used redundantly in one system. In addition, the MCH provides an Ethernet interface as management interface with extensive options.

The PIGMG MTCA.0 R1.0, Micro Telecommunications Computing Architecture Base Specification of 6 July, 2006 and the PCIMG MTCA.4 R1.0, MicroTCA Enhancements for Rear I/O and Precision Timing of 22 August, 2011 currently apply (January 2015).

## MTCA.4

The MTCA 4 specification describes the enhancements of the MTCA standard required by scientists in high energy physics for their applications. Along with establishing a unified board format (double mid-size), so-called rear transition modules ( $\mu$ RTM) have also been defined. In this way the conversion and signal conditioning part can be uncoupled from the data processing area. The larger board surface also allows more complex card designs to be implemented for high performance analogue/digital converters. An additional backplane allows high performance FPGA modules to communicate with each other without latency.

Of course, AMC.0-compatible modules can also be used in MTCA.4 systems and there is a corresponding splitter kit for this purpose. This modularity and the larger board sizes allow these systems to also be used in a wide range of other fields of application outside of research where they are used with success.



Scalable AdvancedMC based systems – From multi processor system to complex machine control

# MTCA.4 Starter Kits

## MTCA-6P

2U 19" 6 Slot Starter Kit, special Clock Module, PCIe Gen 3



powerBridge  
Computer

2U 19" 6 slot MTCA.4 crate, 6 double mid size AMC slots, 4  $\mu$ RTM slots for Rear I/O, MCH & PM slots, NAT-MCH-PHYS or NAT-MCH-PHYS80, AM G64/471, 256GB SSD, 600W AC PSU

### Ordering Information

MTCA-6P-PH1080a 6 Slot 2U 19" MTCA.4 Starter Kit, NAT-MCH-PHYS80, front to left air flow, NAT-PM-AC600D

MTCA-6P-PH1080b 6 Slot 2U 19" MTCA.4 Starter Kit, NAT-MCH-PHYS80, right to left air flow, NAT-PM-AC600D

MTCA-6P-PH10c 6 Slot 2U 19" MTCA.4 Starter Kit, NAT-MCH-PHYS, right to left air flow with more powerful fan units, NAT-PM-AC600D

## MTCA-12S-PH1080-COM

9U 19" 12 Slot Starter Kit, special Clock Module, PCIe Gen 3



powerBridge  
Computer

9U 19" 12 slot MTCA.4 crate, 12 double mid size AMC slots, 2 MCH & 4 PM slots, NAT-MCH-PHYS80, NAT-MCH-RTM with NAT-MCH-COMex: Quad Core Xeon E3-1505Lv5, 16GB RAM, 256GB SSD, 4x 600W AC PSU

### Ordering Information

MTCA-12S-PH1080-COM 12 Slot 9U 19" MTCA.4 Starter Kit, 4x NAT-PM-AC600D

## MTCA-7S

5U 7 Slot Starter Kit, special Clock Module, PCIe Gen 3



powerBridge  
Computer

5U 7 slot MTCA.4 crate, 6 double mid size AMC slots and  $\mu$ RTM slots, 1 double full size AMC and  $\mu$ RTM slots, MCH & PM slots, NAT-MCH-PHYS, AM G64/471, 256GB SSD, 600W AC PSU

### Ordering Information

MTCA-7S-PH10a 7 Slot 5U 42HP MTCA.4 Starter Kit, NAT-PM-AC600D

## MTCA-12S-PH10a

9U 19" 12 Slot LLRF Starter Kit, special Clock Module, PCIe Gen 3



powerBridge  
Computer

9U 19" 12 slot MTCA.4 LLRF crate, 12 double mid size AMC slots, 2 MCH & 4 PM slots, NAT-MCH-PHYS, AM G64/471, 256GB SSD, 1000W AC PSU, prepared for a RF backplane

### Ordering Information

MTCA-12S-PH10a 12 Slot 9U 19" MTCA.4 LLRF Starter Kit, W-IE-NE-R 1000W

More Starter Kits upon request



Fig.: Fully functional timing/LLRF control system based on MTCA.4 installed in FLASH (Free electron Laser in Hamburg). Generation of ultra-short laser pulses (4.1 nm).

The European XFEL is a 3.4 km long particle accelerator whose control needs to be synchronised along its entire length. To do this DESY requires very reliable, high-performance technology with long-term availability that is also available for the planned 15-year duration of the project. In the same way, management capability, such as the start-up in the ongoing operation, and extremely short latency are further requirements for this experiment.

Only one type of technology can be considered under these conditions: MicroTCA!

High channel densities, redundancies, the monitoring of every component in the system and high-speed links are brought together in this industry standard.

# MicroTCA Chassis

## RackPak/M9-01

6U 9 Slot MicroTCA System



9 full size AMC slots, 2 power module slots, 2 MCH slots

### Ordering Information

RackPak/M9-01 9 Slot MicroTCA System

## RackPak/M6-01

3U 6 Slot MicroTCA System



4 double and 2 single full size AMC slots, 2 Power Module slots, 2 MCH slots

### Ordering Information

RackPak/M6-01 6 Slot MicroTCA System

## RackPak/M2-01

1U 2 Slot MicroTCA System with eMCH



2 single full size or mid size AMC slots, integrated eMCH, integrated 150W AC power supply with wide range AC input and DC output

### Ordering Information

RackPak/M2-01 2 Slot MicroTCA System

## RackPak/M2-02

1U 2 Slot AdvancedMC System



2 single full size AMC slots, 150W AC power supply, direct connection of all ports between both AMCs, data transfer rates up to 10 Gbps per port

### Ordering Information

RackPak/M2-02 2 Slot AdvancedMC System

## RackPak/M6-02

1U 6 Slot MicroTCA System



6 single mid size AMC slots, 1 single full size MCH slot, 250W AC power supply, PCIe on ports 4-7

### Ordering Information

RackPak/M6-02 6 Slot MicroTCA System

## Blu!eco

5 Slot MicroTCA Developmentssystem



3 mid size and two full size slots, MCH slot, IPMI power distribution module integrated on the backplane, plug-in AS PSU 300W 12V output voltage, cooling unit with IPMI support on the backplane, direct SATA / SAS connections, single star topology, optimized high-speed routing

### Ordering Information

Blu!eco 5 Slot MicroTCA System

## NATIVE-C1

1U 6 Slot MicroTCA System with JSM Slot



6 single mid size AMC slots, 1 power module slot, 1 single full size MCH slot, 1 JTAG switch module (JSM) slot, 2 hot swapp cooling units, point-to-point SATA/SAS port 2 & 3, replaceable backplane

### Ordering Information

NATIVE-C1 6 Slot MicroTCA System



# MTCA.4 Chassis

## RackPak/M4-2

2U 6 Slot MTCA.4 Crate



2U 19" 6 slot MTCA.4 Crate, 6 double mid size AMC slots, 4  $\mu$ RTM slots for Rear I/O, MCH & PM slots

### Ordering Information

RackPak/M4-2F 6 Slot 19" MTCA.4 Crate, front to left air flow  
 RackPak/M4-2R 6 Slot 19" MTCA.4 Crate, right to left air flow

## RackPak/M5-1

2U 6 Slot MTCA.4 Crate with JSM Slot



Optical uplink for PCIe (Gen 3) with 8 lanes



2U 19" 6 slot MTCA.4 Crate, 5 double mid size and 1 double full size AMC slots, 5  $\mu$ RTM slots for Rear I/O, MCH with RTM slot, JSM & PM slot, opt. White Rabbit

### Ordering Information

RackPak/M5-1F 6 Slot 19" MTCA.4 Crate, front to left air flow  
 RackPak/M5-1R 6 Slot 19" MTCA.4 Crate, right to left air flow  
 RackPak/M5-1RS RackPak/M5-1R with more efficient fans

## MTCA-12S-RF2

9U 19" 12 Slot LLRF MTCA.4 Crate



9U 19" 12 slot MTCA.4 LLRF Crate, 12 double mid size AMC slots, 2 MCH + 4 PM slots, ready for an LLRF backplane

### Ordering Information

MTCA-12S-RF2 12 Slot 9U 19" MTCA.4 LLRF Crate

## RackPak/M7-40

5U 7 Slot MTCA.4 Crate



5U 7 slot MTCA.4 Crate, 6 double mid size AMC slots and  $\mu$ RTM slots, 1 double full size AMC and  $\mu$ RTM slots, MCH & PM slot

### Ordering Information

RackPak/M7-40 7 Slot 5U 42HP MTCA.4 Crate

## RackPak/M12-41 and RackPak/M12-42

9U 19" 12 Slot MTCA.4 Crate with opt. JSM Slot



9U 19" 12 slot MTCA.4 Crate, 12 double mid size AMC slots, 2 MCH & 4 PM slots, opt. JSM slot and White Rabbit support

### Ordering Information

RackPak/M12-41 12 Slot 9U 19" MTCA.4 Crate  
 RackPak/M12-42 12 Slot 9U 19" MTCA.4 Crate with JSM slot

## RackPak/M2-40

1U 4 Slot MTCA.4 System with eMCH



1U 4 Slot MTCA.4 System, 2 double mid size and 2 single mid size AMC slots, 2 double mid size RTM slots, integrated eMCH, integrated 400W AC power supply with wide range AC input

### Ordering Information

RackPak/M2-40 4 Slot 1U MTCA.4 System with eMCH

## RackPak/M12-43

7U 19" 12 Slot MTCA.4 Crate with JSM Slot



9U 12 slot MTCA.4 Crate with JSM slot, 12 double full size AMC slots, 6 double full size RTM slots, 2 MCH slots, 4/2 PM slots, 2 hot swapp fan units with cooling unit manager, bottom to top air flow

### Ordering Information

RackPak/M12-43 12 Slot 7U 19" MTCA.4 Crate

## RackPak/M12-44

9U 19" 12 Slot MTCA.4 Crate with JSM Slot



9U 12 slot MTCA.4 Crate with JSM slot, 12 double full size AMC slots, 6 double full size RTM slots, 2 MCH slots, 4/2 PM slots, 2 hot swapp fan units with cooling unit manager, front to rear air flow

### Ordering Information

RackPak/M12-44 12 Slot 9U 19" MTCA.4 Crate with JSM slot

# MicroTCA Carrier Hubs

## NAT-MCH

GbE, PCIe, SerialRapid IO, 10GbE MCH



MicroTCA Carrier Hub, 200 MHz Freescale ColdFire 547x CPU with 64MB SDRAM and 32 MB flash, management for up to 12 AMCs, 2 cooling units and 1-4 power units, GbE switch, one Fast Ethernet management port, one GbE port and one clock I/O on BNC port in the front panel

### Ordering Information

|                |                                     |
|----------------|-------------------------------------|
| NAT-MCH-202201 | NAT-MCH-Base12-GbE-SSCH-PCIx48-FP1D |
| NAT-MCH-200004 | NAT-MCH-Base12-GbE-FP0S             |

## NAT-MCH-PHYS

GbE, PCIe MCH



MicroTCA Carrier Hub, management for 12 AMCs, 2 cooling units and 1-4 power units, 16 port GbE switch, 48 port PCIe Gen 3 switch, two GbE ports, USB, RS-232 in the front panel, 128 GB 2,5" SSD or two 1,25" SSD (RAID)

### Ordering Information

|              |   |
|--------------|---|
| NAT-MCH-PHYS | NAT-MCH, 16 GbE, PCIe x4, low jitter Clock Module, double full size |
|--------------|---|

## NAT-MCH-PHYS80

GbE, PCIe MCH



Optical uplink for PCIe (Gen 3) with 16 lanes

MicroTCA Carrier Hub, management for 12 AMCs, 4 cooling units, 4 power units, and 2 rear power units, 16 Port GbE switch, 80 port PCIe Gen 3 switch, two GbE ports, USB, RS-232 in the front panel, front panel optical uplink for PCIe (Gen 3) with 16 lanes, 128 GB 2,5" SSD or two 1,25" SSD (RAID)

### Ordering Information

|                      |   |
|----------------------|---|
| NAT-MCH-PHYS80       | NAT-MCH, 16 GbE, PCIe x4, 80 PCIe Links, low jitter Clock Module, double full size                        |
| NAT-MCH-PHYS80-UPLNK | NAT-MCH, 16 GbE, PCIe x4, 80 PCIe Links, 16 optical PCIe Lanes, low jitter Clock Module, double full size |

## NAT-MCH-RTM

RTM for MTCA.4 Systems and COM Express Carrier




RTM and COM Express type 6 (PCIe x16 Gen 3) carrier for MTCA.4.1 μRTM backplane and LLRF backplane control, 2 DisplayPorts, 4 USB 3.0 and GbE port on the rear panel, zone 3 connector, opt. quad core 2.0 GHz Intel Xeon E3-1505LV5, up to 16GB DDR3 RAM

### Ordering Information

|                                      |  |
|--------------------------------------|--|
| NAT-MCH-RTM                          | RTM and COM Express Carrier Module, double full size                               |
| NAT-MCH-RTM-BM                       | NAT-MCH-RTM plus backplane management, zone 2 connector for μRTM (LLRF) backplanes |
| NAT-MCH-RTM-BM-FPGA                  | NAT-MCH-RTM-BM plus ZYNQ FPGA for eRTMs  |
| OrderAddOn-COMex-F3                  | COM Express type 6 Module with quad core Xeon E3 with up to 16GB RAM               |
| other COM Express modules on request |  |

## MicroTCA System Block Diagram



MicroTCA brings together serial high-speed links, system monitoring, efficient cooling and redundancy strategies in one industry standard.

This standard contains a backplane-based system with a central monitoring unit, MicroTCA Carrier Hub (MCH), 1-2 fan units (CU), up to 4 power supply units (PM) and a maximum of 12 AdvancedMC Modules (AMC).

The PM, CU and MCH power up when the system is switched on. After the MCH has booted up it takes over the control of the PM, controls the CUs and checks the AMC modules in place.

Provided the AMC module information is correct, it operates the high-speed links between the modules (fat pipe). If sufficient power is available in the system the MCH switches on the payload power for the individual AMC modules.



# AdvancedMC CPU Modules x86

## AM G6x/msd

Intel Xeon E3-1505M v6/Core i3 Gen. 7 CPU



Optical uplink for PCIe (Gen 3) with 8 lanes



Processor AMC with Intel Xeon E3-1505M v6 or Intel Core i3-7102E CPU, Intel CM238 chipset, up to 32 GB DDR4 RAM, DisplayPort, GbE, SATA, M.2 SSD, RS-232, USB, AMC.1 type 8 or type 4, AMC.2 E2 (2x GbE) and AMC.3 S2 (SATA), TCLKA clock input, audio, opt. 10 GbE, opt. FIN-S software, -25°C .. +70°C operating temperature

### Ordering Information

|            |   |
|------------|---|
| AM G6x/msd | 4 Core Intel Xeon E3-1505M v6 AMC CPU, double mid size  |
| AM G6x/msd | 4 Core Intel Xeon E3-1505M v6 AMC CPU, double full size |
| AM G6x/msd | 2 Core Intel Core i3-7102E AMC CPU, double mid size     |
| AM G6x/msd | 2 Core Intel Core i3-7102E AMC CPU, double full size    |

## AM F5x/msd

Intel Xeon E3-1500 v5 CPU with PCIe Fabric



Processor AMC with Intel Xeon E3-1500 v5 CPU, Intel CM236 chipset, 16 GB RAM, 10GbE, DisplayPort, GbE, SATA, RS-232, USB, AMC.1 type 8 or type 4, AMC.2 E2 (2x GbE) and AMC.3 S2 (SATA), PCIe Fabric, TCLKA clock input

### Ordering Information

|            |  |
|------------|--|
| AM F51/msd | 4 Core, 2.8 GHz E3-1515M v5, 16 GB RAM, mid size |
| AM F52/msd | 4 Core, 2.8 GHz E3-1505M v5, 16 GB RAM, mid size |
| AM F53/msd | 4 Core, 2.8 GHz E3-1505L v5, 16 GB RAM, mid size |

## AM E4x/msd

Intel Xeon D-1500 CPU with PCIe Fabric



Processor AMC with Intel Xeon D-1500 CPU, 32 GB RAM, 10GbE, DisplayPort, GbE, SATA, RS-232, USB, AMC.1 type 8 or type 4, AMC.2 E2 (2x GbE) and AMC.3 S2 (SATA), PCIe Fabric, TCLKA clock input

### Ordering Information

|            |  |
|------------|--|
| AM E41/msd | 8 Core, 1.6 GHz D-1539, 32 GB RAM, mid size  |
| AM E42/msd | 12 Core, 1.5 GHz D-1559, 32 GB RAM, mid size |

## AM C1x/msd

Intel Core i7 4 Generation CPU with Serial RapidIO Fabric



Processor AMC with Intel Core i7 CPU, Intel QM87 chipset, up to 16 GB RAM, GbE, SATA, RS-232, AMC.2 E2 (2x GbE), AMC.3 S2 (SATA) and AMC.4 type 5 and 10 (one or two x4 Serial RapidIO), TCLKA clock input

### Ordering Information

|               |   |
|---------------|---|
| AM C1x/msd-yz | 2 Core, Core i5-4410E, 4 GB RAM, full size  |
| AM C1x/msd-yz | 2 Core, Core i5-4410E, 4 GB RAM, mid size   |
| AM C1x/msd-yz | 4 Core, Core i7-4700EQ, 4 GB RAM, full size |
| AM C1x/msd-yz | 4 Core, Core i7-4700EQ, 4 GB RAM, mid size  |

# AdvancedMC CPU Modules ARM

## NAT-AMC-LX2

ARM NXP LX2160A CPU



Processor AMC with NXP LX2160A ARM CPU, up to 64 GB DDR4 RAM, 128 MB QSPI, up to 128 GB eMMC, M.2 slot for PCIe x4 or SATA SSD or USB 3.0/PCIe x4 extension, MicroSD slot, 100GbE QSFP port or 2 50GbE ports or 4 25GbE ports, USB 3.0, USB-C console port, AMC.1 type 4 and AMC.2 type E2 and type 5

### Ordering Information

|               |   |
|---------------|---|
| NAT-AMC-LS2-F | 16 Core A72, 2.2 GHz LX2160A ARM, full size |
| NAT-AMC-LS2-F | 16 Core A72, 2.2 GHz LX2160A ARM, mid size  |

# AdvancedMC I/O Modules – Field Bus

## BU-65590A

MIL-STD-1553 and ARINC 429 Controller



2 or 4 channel MIL-STD-1553 interface, redundant channels, BC, RT, MT or RT/MT, ARINC 429 interface with 8 receive and 4 transmit channels, 2 RS-232 channels, 2 RS-422/485 channels, 6 prog. digital I/Os, 1 MB RAM per MIL-STD-1553 channel, IRIG-B time code input, 48-bit/1µs time stamp, DMA engine, front Micro-D connector, AMC.1 type 4, opt. Conformal Coating

### Ordering Information

|            |   |
|------------|---|
| BU-65590A0 | MIL-STD-1553, ARINC 429 Controller, mid size  |
| BU-65590A1 | MIL-STD-1553, ARINC 429 Controller, full size |

## CAN-4

4 Channel CAN Interface



4 high-speed CAN interfaces, 11bit and 29bit CAN IDs, Spartan-3e FPGA, up to 1 Mbit/s bit rate, receive buffer, prog. error warning limit, listen only mode, aut. bit rate detection, interfaces potential isolated against each other, 4 front RJ45 connectors, 11898-1 (CAN 2.0A/B) compliant, AMC.1 type 1

### Ordering Information

|                       |  |
|-----------------------|--|
| CAN-4f                | 4 Channel CAN Interface, full size     |
| CAN-4m                | 4 Channel CAN Interface, mid size      |
| AMC-CAN4-DSUB-Adapter | RJ45-to-9-pin DSUB Adapter cable, 1,5m |

## NAMC-ECAT

EtherCAT Slave Module



EtherCAT Slave module, 3 front RJ45 connectors, ET1100 slave controller, AMC.1 type 1

### Ordering Information

|            |                                  |
|------------|----------------------------------|
| NAMC-ECATf | EtherCAT Slave Module, full size |
| NAMC-ECATm | EtherCAT Slave Module, mid size  |



### Features

- Configuration and management of EtherCAT networks
- Cyclic exchange of process data
- Sophisticated API common to all implementations as interface between the application and the EtherCAT master stack
- Mailbox based communication:
  - CAN application protocol over EtherCAT (CoE)
  - Ethernet over EtherCAT (EoE)
  - File over EtherCAT (FoE)
  - Servo Drive over EtherCAT (SoE)
- Built-in detailed diagnostics and profiling functions
- Written in ANSI-C designed for high performance, small resource usage and scalability
- Core components of the stack software are operating system and CPU architecture independent
- Adaption to many prevalent (real-time) operating systems available from stock
- EtherCAT Master Class A according to ETG.1500

## EPS-9905

EtherCAT Solution



EtherCAT Chassis with 5 slots, slave module status monitoring, IP31, 50G shock resistance, 6.6W power consumption, small dimensions 130 x 110 x 105 mm, -20°C .. +60°C operating temperature range

### Ordering Information

|          |                                    |
|----------|------------------------------------|
| EPS-9905 | EtherCAT chassis for Slave Modules |
| EPS-6000 | EtherCAT Bus Coupler               |

## EtherCAT Slave Modules Overview for EPS-9905

|          |   |
|----------|---|
| EPS-1032 | 32 Channel Sourcing Type Digital Input  |
| EPS-1132 | 32 Channel Sinking Type Digital Input   |
| EPS-2032 | 32 Channel Sourcing Type Digital Output |
| EPS-2132 | 32 Channel Sinking Type Digital Output  |
| EPS-2308 | 8 Channel Relay Output                  |
| EPS-3032 | 32 Channel ±10V Analog Input            |
| EPS-3216 | 16 Channel 0-20mA Analog Input          |
| EPS-3504 | 4 Channel RTD Thermal Input             |
| EPS-4008 | 8 Channel +/-10V Analog Output          |
| EPS-7002 | 2 Channel Pulse-Train Motion Control    |



# AdvancedMC I/O Modules – PMC Carrier

## TAMC260

AMC Module with one PMC Slot



AMC carrier module for one PMC module, front and P14 I/O via 68-pol. SCSI-V connector, AMC.1 type 1, -40°C .. +85°C operating temperature range

### Ordering Information

|             |  |
|-------------|--|
| TAMC260-10R | AMC Carrier for 1 PMC Module, 5V, double full size   |
| TAMC260-11R | AMC Carrier for 1 PMC Module, 3.3V, double full size |
| TAMC260-20R | AMC Carrier for 1 PMC Module, 5V, double mid size    |
| TAMC260-21R | AMC Carrier for 1 PMC Module, 3.3V, double mid size  |

## NAMC-PMC

AMC Module with one PMC Slot



AMC carrier module for one PMC module, front I/O, AMC.1 type 1, 0°C .. +55°C operating temperature range

### Ordering Information

|          |   |
|----------|---|
| NAMC-PMC | AMC Carrier Module for 1 PMC Module, mid size |
|----------|---|

## TAMC261 and TAMC020

AMC Module with one PMC Slot and MTCA.4 µRTM



AMC carrier module for one PMC module with MTCA.4 Rear I/O, front and P14 I/O, AMC.1 type 1, -40°C .. +85°C operating temperature range

### Ordering Information

|                |  |
|----------------|--|
| TAMC261-10R    | AMC Carrier Module for 1 PMC Module with MTCA.4 Rear I/O, double mid size            |
| TAMC261-11R    | AMC Carrier Module for 1 PMC Module, with MTCA.4 Rear I/O, double full size          |
| TAMC261-20R    | AMC Carrier Module for 1 PMC Module, with MTCA.4 Rear I/O, M-LVDS, double mid size   |
| TAMC261-21R    | AMC Carrier Module for 1 PMC Module, with MTCA.4 Rear I/O, M-LVDS, double full size  |
| TAMC020-TM-10R | MTCA.4 µRTM for Rear I/O access to the PMC back I/O lines, double mid size, PIM I/O  |
| TAMC020-TM-11R | MTCA.4 µRTM for Rear I/O access to the PMC back I/O lines, double full size, PIM I/O |

On our website [www.powerbridge.de](http://www.powerbridge.de) you can find more than 100 PMC Modules

# AdvancedMC I/O Modules – FPGA

## MFMC

Xilinx Artix-7 FPGA Module for MTCA.4 Rear-I/O with 2 FMC slots



Xilinx Artix-7 FPGA, MTCA.4 Rear I/O, two FMC slots, VITA 57.1, 16 GB DDR3 RAM, 256 MB quad flash, front SMB, MicroUSB, PCIe x4, GbE

### Ordering Information

|           |   |
|-----------|---|
| MFMC-16G1 | Dual FMC Carrier Module, Artix-7 XC7A200T-1, 16 GB RAM, double mid size |
| MFMC-16G2 | Dual FMC Carrier Module, Artix-7 XC7A200T-2, 16 GB RAM, double mid size |
| MFMC-4G2  | Dual FMC Carrier Module, Artix-7 XC7A200T-2, 4 GB RAM, double mid size  |

## FMC Modules Overview

|                   |  |
|-------------------|--|
| FMC-4SFP+         | Quad SFP/SFP+ Ports                          |
| FMC-CAMERALINK    | High-performance 2-fach CameraLink Interface |
| FMC-CL            | High-performance 2-fach CameraLink Interface |
| FMC-MOTDRV22      | Dual Channel Stepper Motor Driver            |
| FMC-Pico-1M4      | Quad 16/20-bit 1 MSPS Pico-Ammeter           |
| IC-ADC-FMca       | Quad 16-bit ADC, 135 MSPS                    |
| IC-ADC-FMcb       | Quad 14-bit ADC, 400 MSPS                    |
| IC-ADC-FMcc       | Quad 12-bit ADC, 1.6 GSPS                    |
| IC-DAC-FMca       | Quad 16-bit DAC, 1 GSPS                      |
| IC-QSFP-FMca      | Dual QSFP 10GbE                              |
| IC-SFP-FMca       | Dual SFP+ GbE                                |
| NAT-FMC-4GigE-PoE | Quad GbE with Power over Ethernet            |
| TFMC684           | 32 diff. M-LVDS                              |
| TFMC900           | Test Module, Spartan-2 FPGA                  |

**IC-ADC-FMcc**  
4 Channel ADC, 1.6 GSPS



**TFMC684**  
32 diff. M-LVDS



**FMC-MOTDRV22**  
Dual Channel Stepper Motor Driver





# AdvancedMC I/O Modules – FPGA / ADC / DAQ

## TAMC532

32 port 12/14bit 75/50 MSPS ADC



Kintex-7 FPGA, MTCA.4 Rear I/O,  $\pm 1V$  diff. input, 4 GB DDR3 RAM, AMC.1 type 4, AMC.2 type E1, 2 front SFP+, M-LVDS on AMC ports 17–20, double mid size and double full size form factor

### Ordering Information

|                |  |
|----------------|--|
| TAMC532-10R    | 32 Channel 12bit 75 MSPS ADC, 512 MB RAM, Kintex-7 70T |
| TAMC532-11R    | 32 Channel 14bit 50 MSPS ADC, 512 MB RAM, Kintex-7 70T |
| TAMC532-TM-30R | $\mu$ RTM for TAMC532                                  |
| TA900-10R      | Program and Debug Box                                  |

Kintex-7 160T/325T/410T and other RAM versions on request

## ADQ7DC

14bit Digitizer Module



Optical uplink for PCIe (Gen 3) with 4 lanes



14bit resolution, 1 or 2 analog channels, 5 to 10 GSPS sample rate per channel, DC-coupled with up to 2.5GHz analog BW optimized for low noise, AC-coupled with up to 2.5GHz analog BW optimized for wide band linearity, programmable DC-offset, Multi-unit synchronization, time-stamp for real-time operation, 4GB data memory, 6.8 Gbytes/s with PCIe x8 Gen3, optical 10GbE, GbE, USB 3.0, MTCA.4, double mid size form factor

### Ordering Information

|        |   |
|--------|---|
| ADQ7-F | 14bit Digitizer Module, double mid size |
|--------|---|

## ADQ14

1 to 4 Channel 14bit Digitizer Module



Optical uplink for PCIe (Gen 2) with 4 lanes



14bit resolution, 1 to 4 analog input channels, 500 MSPS to 2 GSPS sample rate per channel, DC-coupling with up to 1.2 GHz analog bandwidth, AC-coupling with up to 1.2 GHz analog bandwidth, time stamp for real-time operation, internal and external trigger, trigger output, Xilinx Kintex-7 K325T FPGA, GbE, MTCA.4, 2GB data memory, programmable DC-offset, multi-channel synchronization, PCIe x4 Gen2, SRIO x4, double mid size form factor

### Ordering Information

|          |   |
|----------|---|
| ADQ14-AC | ADQ14 Digitizer Module, AC-coupled, double mid size |
| ADQ14-DC | ADQ14 Digitizer Module, DC-coupled, double mid size |

## AMC-AD1024-HD50

24 Channel Analogue-Digital-I/O AMC Module



24 TTL digital I/Os, 8 16bit analogue inputs, 2 16bit analogue outputs, 4 RS-485 trigger ports, 7 10-pin Harting har-link connector, Spartan-2 FPGA

### Ordering Information

|                  |  |
|------------------|--|
| AMC-AD1024-HD50f | 24 Channel Analogue-Digital-I/O AMC, full size |
| AMC-AD1024-HD50m | 24 Channel Analogue-Digital-I/O AMC, mid size  |

## AMC-PICO-8

8 Channel Bipolar 20bit Picoammeter with MTCA.4 Rear I/O



8 bipolar current input channels, 20bit resolution, Virtex-5 FPGA for data processing, Spartan-6 FPGA for board management, high resolution multi channel current up to  $\pm 1mA$ , two independent full-scale ranges ( $\pm 1mA$  and  $\pm 1\mu A$ ), up to 1 MSPS simultaneous and independent sampling, low conversion time delay, low noise, low temperature dependence, external clock input on the front panel, MTCA.4, Zone3 Class D1.1 compatible, double full size form factor

### Ordering Information

|            |   |
|------------|---|
| AMC-PICO-8 | 8 Channel 20bit Picoammeter, double full size |
|------------|---|

## DAMC-FMC20

Dual (HPC + LPC) FMC Carrier with MTCA.4 Rear I/O



1 HPC and 1 LPC FMC slot, 2 Spartan-6 FPGAs, MTCA.4, one serial link (GTP) for each FMC module, one additional 12V power connector for high current FMC applications, AMC.1 type 1 PCIe, Zone3 Class D1.1 compatible, double mid size form factor

### Ordering Information

|            |                                   |
|------------|-----------------------------------|
| DAMC-FMC20 | Dual FMC Carrier, double mid size |
|------------|-----------------------------------|

# AdvancedMC I/O Modules – FPGA / ADC / DAQ

## DAMC-FMC2ZUP

Ultrascale+ FMC+ Carrier with MTCA.4 Rear I/O



1 FMC+ slot and 1 HPC FMC slot, Xilinx UltraScale+ FPGA with 1.5GHz 4 core ARM Cortex-A53, MTCA.4, 64-bit 4GB DDR4 RAM, 16-bit 1GB DDR4 RAM, White Rabbit support, SD slot, 8GB eMMC, Front USB-C with DisplayPort and USB 3.0, AMC.1 type 8 PCIe, Zone3 Class D1.1 compatible, double mid size form factor

### Ordering Information

DAMC-FMC2ZUP Ultrascale+ FMC+ Carrier, double mid-size

## DAMC-FMC25

Dual (HPC) FMC Carrier with MTCA.4 Rear I/O



2 HPC FMC slots, Xilinx Virtex-5 with 256MB DDR2 RAM and Spartan-6 XC6SLX45T-3FGG484C FPGA with 128MB DDR2 RAM, external clock input (SMA), SMA and Micro-USB port on the front panel, MicroSD slot, 2 temperature sensors, 77 Diff. Pairs and 2 GTX @ 6.5 Gbit/s fast links to each FMC, 42 Diff. Pairs and 2 GTX @ 6.5 Gbit/s fast links to RTM, 4 low latency links, AMC.1 type 4 PCIe Gen1, MTCA.4, Zone3 Class D1.1 compatible, double mid size form factor

### Ordering Information

|              |   |
|--------------|---|
| DAMC-FMC25-1 | 2 FMC Carrier, XC5VFX70T-1FFG1136C, Virtex-5 Speed Grade up to 4.25 Gbit/s, double mid size |
| DAMC-FMC25-2 | 2 FMC Carrier, XC5VFX70T-2FFG1136C, Virtex-5 Speed Grade up to 6.5 Gbit/s, double mid size  |

## HV-PANDA

4 High Voltage Channel AMC Module with MTCA.4 Rear I/O




4 high voltage (HV) channels with SHV ports, 6kV, 4kV or 500V output voltage, positive or negative polarity, floating return per pair of channels rated up to  $\pm 20V$  with respect to protective earth (PE), nominal voltage accuracy better than 0,05%, current and voltage limits can be changed in real-time, behavior change of the channels when the current limit threshold is exceeded in real-time, 1V/s to 500V/s ramp speed range configurable with 1V/s resolution, 0,01% output voltage and current readback resolution, interconnections between CPU and HV channels, infrastructure for management of RTM boards, PCIe x1, MTCA.4, Zone3 Class D1.1 compatible, double full size form factor

### Ordering Information

|            |  |
|------------|--|
| HVPANDA6KP | 4 Channel HV AMC, 6kV@6W channel, double full size     |
| HVPANDA6KN | 4 Channel HV AMC, -6kV@6W channel, double full size    |
| HVPANDA4KP | 4 Channel HV AMC, 4kV@7W channel, double full size     |
| HVPANDA4KN | 4 Channel HV AMC, -4kV@7W channel, double full size    |
| HVPANDA05P | 4 Channel HV AMC, 500V@1,5W channel, double full size  |
| HVPANDA05N | 4 Channel HV AMC, -500V@1,5W channel, double full size |

## PRTM-PZDR4

4 Channel Piezodriver/sensor Module



4 channel piezodriver/sensor module, 80kHz small signal bandwidth for 1 $\mu$ F load, remotely switchable actuator and sensor functionality, DAC and ADC for fast control and monitoring up to 200 kSPS per channel, 0 .. +100V unipolar or  $\pm 100V$  piezo power supplies, external or internal piezo power supply, digital monitoring of input, output voltage and output current, interlock signal support, 1 kHz, 50 kHz, 100 kHz, 150 kHz low pass frequency range, laser oscillator or piezo tuner MTCA.4, Zone3 Class D1.0-2 compatible, double mid size form factor

### Ordering Information

PRTM-PZDR4 4 Channel Piezodriver Module, double mid size

# AdvancedMC I/O Modules – FPGA / ADC / DAQ

## SIS8160

Kintex Ultrascale FPGA based dual HPC FMC Carrier



Xilinx Kintex Ultrascale XCKU040-1FFVA1156C or XCKU060-1FFVA1156C FPGA, 4GB DDR4 RAM, 2 high pin count (HPC) FMC slots, two 256 Mbit SPI boot proms, 2 SFP+ ports, 4 PCIe Gen3 lanes, 12V standalone operation, White Rabbit option

### Ordering Information

|            |                               |
|------------|-------------------------------|
| SIS8160-40 | XCKU040 FPGA, double mid size |
| SIS8160-60 | XCKU060 FPGA, double mid size |

## SIS8300-L

10 Channel 125 MSPS Digital-Analogue-I/O AMC Module for MTCA.4 Rear I/O



10 channel 125 MSPS 16bit ADC, MTCA.4 Rear I/O, 10 – 125 MSPS sampling rate, 2 16bit DACs, 2 front SFP, 2GB DDR3 RAM, Virtex-6 XC6VLX130T-2FFG1156C FPGA, 1 GSample memory, dual boot, in-field firmware upgrade support

### Ordering Information

|                  |  |
|------------------|--|
| SIS8300-L        | 10 Channel 16bit ADC, double mid size  |
| SIS8300-L25AC5DC | 5 Channel 16bit AC ADC and 5 Channel 16bit DC ADC, DAC to front panel, Zone3 Class A1.1C0, double mid size |
| SIS8300-L28AC2DC | 8 Channel 16bit AC ADC and 2 Channel 16bit DC ADC, DAC to Zone3, Zone3 Class A1.1C0, double mid size       |

## SIS8325

10 Channel 250 MSPS Digital-Analogue-I/O AMC Module for MTCA.4 Rear I/O



10 channel 250 MSPS 16bit ADC, MTCA.4 Rear I/O, 10 – 250 MSPS sampling rate, 2 16bit DACs, 2 front SFP, 2GB DDR3 RAM, Virtex-6 FPGA, 1 GSample memory, dual boot, in-field firmware upgrade support

### Ordering Information

|         |                                       |
|---------|---------------------------------------|
| SIS8325 | 10 Channel 16bit ADC, double mid size |
|---------|---------------------------------------|

## SIS8300-KU

10 Channel 125 MSPS Digital-Analogue-I/O AMC Module for MTCA.4 Rear I/O



10 channel 125 MSPS 16bit ADC, MTCA.4 Rear I/O, 10 – 125 MSPS sampling rate, 2 16bit DACs, 2 front SFP, 2GB DDR3 RAM, Xilinx Kintex Ultrascale XCKU040-1FFVA1156C FPGA, 1 GSample memory, dual boot, in-field firmware upgrade support, Zone3 Class A1.1C0 compatible, White Rabbit option

### Ordering Information

|                     |  |
|---------------------|--|
| SIS8300-KU10AC      | 10 Channel 16bit AC ADC, DAC to front panel, double mid size                                   |
| SIS8300-KU10DC      | 10 Channel 16bit DC ADC, DAC to front panel, double mid size                                   |
| SIS8300-KU8AC2DCDFP | 8 Channel 16bit AC ADC and 2 Channel 16bit DC ADC, DAC to front panel, double mid size         |
| SIS8300-KU8AC2DCDZ3 | 8 Channel 16bit AC ADC and 2 Channel 16bit DC ADC, DAC to Zone3, double mid size               |
| SIS8300-KU8AC2DCWR  | 8 Channel 16bit AC ADC and 2 Channel 16bit DC ADC, DAC to Zone3, White Rabbit, double mid size |

## RTM Overview for SIS8300-L and SIS8300-KU

|              |  |
|--------------|--|
| SIS8900      | Single ended input card                |
| RTM7201      | 4 channel signal modulator             |
| DWC8300      | 10 channel downconverter               |
| BPM          | Interleaved sampling for BPM readout   |
| APD          | Dual channel signal stretcher          |
| DWC8VM1      | 8 channel downconverter, 1 channel VM  |
| DS8VM1       | 8 channel analogue input, 1 channel VM |
| Fast ADC RTM | LLRF ADC frontend                      |





# AdvancedMC I/O Modules – FPGA / ADC / DAQ

## SIS8864

64 Channel Digital–Analogue–I/O Artix-7 FPGA based AMC Module



64 channel 32bit DAC, Artix-7 XC7A15T-2FGG484C FPGA, PCIe Gen2, LVTTTL with TTL tolerance, one LEMO LVTTTL control input with TTL tolerance, one LEMO LVTTTL control output, interrupt generation, 4 MLVDS  $\mu$ TCA ports, 8 MLVDS lines

### Ordering Information

SIS8864 64 Channel 32bit DAC, Artix-7 FPGA, double mid size

## SIS8800

Histogramming Scaler/Multiscaler/Counter AMC Module with MTCA.4 Rear I/O



16 front counter channel histogramming Scaler/Multiscaler/counter, MTCA.4 Rear I/O, up to 200 MHz count rate, 4 control inputs and 4 control outputs, 2GB RAM, Virtex-6 FPGA, GbE, 4 PCIe lanes, in-field firmware upgrade support

### Ordering Information

SIS8800EFT Histogramming Scaler/Multiscaler/Counter, ECL and flat cable TTL, double mid size

SIS8800NLT Histogramming Scaler/Multiscaler/Counter, NIM and LEMO TTL, double mid size

# AdvancedMC I/O Modules – DSP / FPGA

## NAMC-ARRIA10-FMC

FMC Carrier AMC Module with Intel Arria10 FPGA



Intel Arria10 GX1150, GX900, GX660, GX570, SX660 or SX570 FPGA, FMC slot, 16GB DDR4 RAM, up to 256MB flash, 1.5 GHz dual core ARM Cortex A9 CPU, MicroSD slot, AMC.1, AMC.2, AMC.3, AMC.4, GbE, PCIe, SATA, SAS, SRI0 via backplane, TCLKA-D, FCLKA, opt. -40°C .. +100°C operating temperature range

### Ordering Information

NAMC-ARRIA10-FMC-G105 FPGA Module, ARRIA10 GX1150, mid size

NAMC-ARRIA10-FMC-G090 FPGA Module, ARRIA10 GX900, full size

NAMC-ARRIA10-FMC-G066 FPGA Module, ARRIA10 GX660, mid size

NAMC-ARRIA10-FMC-G057 FPGA Module, ARRIA10 GX570, mid size

NAMC-ARRIA10-FMC-S066 FPGA Module, ARRIA10 SX660, mid size

NAMC-ARRIA10-FMC-S057 FPGA Module, ARRIA10 SX570, mid size

## NAMC-ODSP-M

Media Accelerator AMC module with up to 8 DSPs



Media accelerator AMC module with up to 8 Octasic OCT2224M DSPs with 24 cores, 512 MB RAM for each DSP, Kintex-7 FPGA, iTDM, GbE, 10GbE, wide range of audio/video codecs

### Ordering Information

NAMC-ODSP-M-8f ADSP AMC Module, 8 OCT2224M-DSPs, full size

NAMC-ODSP-M-8m ADSP AMC Module, 8 OCT2224M-DSPs, mid size

NFW-ODSP-M-A NAT Firmware with basic audio codecs

NFW-ODSP-M-AV NAT Firmware with audio and video codec

## NAMC-ZYNQP-FMC

FMC Carrier AMC Module with Xilinx ZYNQ-7000 FPGA



Xilinx ZYNQ-7000 XC7Z045 or XC7Z100 FPGA, FMC slot, 1GB 64bit RAM, 512MB 32bit RAM, 256MB flash, MicroSD slot, AMC.1, AMC.2, AMC.3, AMC.4, GbE, PCIe, SRI0, 10GbE via backplane, TCLKA-D, FCLKA

### Ordering Information

NAMC-ZYNQP-FMC-0-045 FPGA Module, Zynq-7000 XC7Z045, mid size

NAMC-ZYNQP-FMC-1-045 FPGA Module, Zynq-7000 XC7Z045, full size

NAMC-ZYNQP-FMC-0-100 FPGA Module, Zynq-7000 XC7Z100, mid size

NAMC-ZYNQP-FMC-1-100 FPGA Module, Zynq-7000 XC7Z100, full size

## NAT-AMC-TCK7

Xilinx Kintex-7 FPGA AMC Module with MTCA.4 Rear-I/O



Xilinx Kintex-7 XC7K355T or XC7K420T FPGA, 16GB DDR3 RAM, 2x 256MB QSPI flash, up to eight 10Gbit/s SFP+ ports, low-latency, MicroUSB, SMB connector, AMC.1 type 4, AMC.2, MTCA.4

### Ordering Information

NAT-AMC-TCK7-355M FPGA Module, Kintex-7 XC7K355T, double mid size

NAT-AMC-TCK7-355F FPGA Module, Kintex-7 XC7K355T, double full size


NAT-AMC-TCK7-420M FPGA Module, Kintex-7 XC7K420T, double mid size

NAT-AMC-TCK7-420F FPGA Module, Kintex-7 XC7K420T, double full size

# AdvancedMC I/O Modules – DSP / FPGA

## IFC-1410

Intelligentes FMC Carrier



1.8 GHz NXP QorIQ T2081, AltiVec Xilinx Kintex UltraScale KU040 or KU060 FPGA, TOSCA III FPGA Design Kit, 2 HPC FMC slots, D1.4 compliant RTM interface, full size and mid size

### Ordering Information

|              |  |
|--------------|--|
| IFC-1410-40m | FMC Carrier, UltraScale KU040, mid size  |
| IFC-1410-40f | FMC Carrier, UltraScale KU040, full size |
| IFC-1410-60m | FMC Carrier, UltraScale KU060, mid size  |
| IFC-1410-60f | FMC Carrier, UltraScale KU060, full size |

## FMC and RTM Overview for IFC-1410 and IFC-1420

|               |  |
|---------------|--|
| ADC_3110/3111 | 8 Channel 16bit 250 MSPS ADC   |
| ADC_3112      | 4 Channel 12bit 1 GSPS ADC or 2 Channel 12bit 2 GSPS DAC                 |
| ADC_3117      | 20 Channel 16bit 5 MSPS ADC and 2 Channel 16bit 1 MSPS DAC               |
| ADC_3210      | Eight 14-bit ADC, 1300/625 MSPS  |
| DAC_3113      | 2 Channel 16bit 250 MSPS ADC and 2 Channel 16bit 250 MSPS DAC            |
| DIO_3118      | 16 TTL Digital In/16 TTL Digital Out, LVDS In/Out, HPC                   |
| RSP_1461      | COM Extender µRTM with 1 SFP GbE, 6 SFP+ 10GbE, 2 SMA and D1.4 Interface |



## IFC-1420

Digitizer AMC Module



1.8 GHz NXP QorIQ T2081, AltiVec Xilinx Kintex UltraScale KU040 or KU060 FPGA, TOSCA III FPGA Design Kit, 10 channel 16bit 250 MSPS ADC (from RTM), 5 channel 16bit DAC (to RTM), 1 HPC FMC slot, A1 compliant RTM interface for analog signals, full size and mid size

### Ordering Information

|              |   |
|--------------|---|
| IFC-1420-40m | Digitizer AMC Module, UltraScale KU040, mid size  |
| IFC-1420-40f | Digitizer AMC Module, UltraScale KU040, full size |
| IFC-1420-60m | Digitizer AMC Module, UltraScale KU060, mid size  |
| IFC-1420-60f | Digitizer AMC Module, UltraScale KU060, full size |

## AMC-4C6678-SRIO

DSP Module with GPS Transceiver and SerialRapidIO



Four TMS320C6678 DSPs with eight 1.25 GHz cores and 8 GB DDR3-1600 SDRAM and 512 MB flash, 640 GFLOPS, 1280 GMACS, 16 Gbit/s Serial RapidIO, Front-GbE, AMC.1 type 4, AMC.2 type E2, AMC.4

### Ordering Information

|                 |                                   |
|-----------------|-----------------------------------|
| AMC-4C6678-SRIO | AMC Module with 4 DSPs, full size |
|-----------------|-----------------------------------|

## AMC-D24A4-RFx

DSP Module with Kintex-7 FPGA, 4 ARM and 24 DSP Cores



Three DSPs, one TM320TCI6636 DSP with eight 1.2 GHz DSP cores, four 1.4 GHz ARM A15 cores and 2 GB DDR3-1600 SDRAM and 256 MB flash, two TMS320C6678 DSPs with eight 1.25 GHz DSP cores and 4 GB DDR3-1333 SDRAM, Kintex-7 FPGA with 1 GB DDR3-1600 SDRAM and 256 MB flash, 20 Gbit/s Serial RapidIO Gen2, opt. 10GbE, 4 front RF channels, RF frequency: 662MHz-3.84 GHz, 3 SFP+ and one USB port, GPS, 2 SMB clock I/O, standalone mode (with just power and cooling) AMC.2 type E2, AMC.4

### Ordering Information

|               |   |
|---------------|---|
| AMC-D24A4-RF4 | AMC with 3 DSPs and RF channels, double full size |
| AMC-D24A4F    | AMC with 3 DSPs, double full size                 |
| AMC-D24A4M    | AMC with 3 DSPs, double mid size                  |

## AMC-K2L-RF2

LTE eNodeB Module with 4 DSPs and 2 ARM CPUs



Four 1.2 GHz C66x DSP cores, two 1.5 GHz ARM15 cores, 2GB RAM, 256MB-flash, 2 RF channels with 700 MHz to 4 GHz frequency, 2 SMA for RF Tx and 2 SMA for RF Rx or TRx ports on the front panel, AMC.1 type 1 and AMC.2 type E2, -40°C .. +70°C operating temperature range, opt. GPS and 2 SMA for RF feedback ports, opt. GbE and timing port, CPRI SFP+ slot, Power over Ethernet and fan control, opt. conduction-cooled

### Ordering Information

|              |   |
|--------------|---|
| AMC-K2L-RF2m | LTE AMC Module, mid size  |
| AMC-K2L-RF2f | LTE AMC Module, GPS, Timing + Feedpack Ports, full size                                   |
| AMC-K2L-MC   | Micro Carrier for AMC-K2L-RF2, GbE Port, CPRI SFP+ slot, Power over Ethernet, fan control |

# AdvancedMC I/O Modules – Telecom

## NAMC-xE1/T1

8 or 16 Channel E1/T1 Communication Controller



8/16 E1/T1 channel or 4 E3/T3 channel, AMC.1 type 1, AMC.2 type E2, SRIO, Lattice ECP3 FPGA with 70.000 logical elements, 32/64-Mbit QDR2 SRAM, TDM-to-I-TDM connector, H.110-alike 32 MHz TDM interface

### Ordering Information

|                |  |
|----------------|--|
| NAMC-4E3/T3-s  | 4 Channel E3/T3 AMC Module, mid size   |
| NAMC-4E3/T3-f  | 4 Channel E3/T3 AMC Module, full size  |
| NAMC-8E1/T1-s  | 8 Channel E1/T1 AMC Module, mid size   |
| NAMC-8E1/T1-f  | 8 Channel E1/T1 AMC Module, full size  |
| NAMC-16E1/T1-s | 16 Channel E1/T1 AMC Module, mid size  |
| NAMC-16E1/T1-f | 16 Channel E1/T1 AMC Module, full size |

## NAMC-SDH

SDH Module



SDH (Synchronous Digital Hierarchy) module for SDH/SONET networks, 4 SFP front-I/O ports, four 155Mbps OC-3/STM1 or two 622Mbps OC-12/STM-4 interfaces, 252 E1 or 336 T1 framers, TDM, iTDM, XILINX Kintex-7 FPGA, TSI and opt. HDLC controller, GbE ports, opt. XAUI, SRIO, full size and mid size

### Ordering Information

|              |  |
|--------------|--|
| NAMC-SDH-114 | SDH Module, 4 STM1 (OC-3), 2x72Mbit QDR2 + SRAM  |
| NAMC-SDH-122 | SDH Module, 2 STM4 (OC-12), 2x72Mbit QDR2 + SRAM |
| NAMC-SDH-214 | SDH Module, 4 STM1 (OC-3), 2 GB DDR3 SRAM        |
| NAMC-SDH-222 | SDH Module, 2 STM4 (OC-12), 2 GB DDR3 SRAM       |

## NAMC-SDR

RF Interface AMC for Software Defined Radio



SDR AMC module, Xilinx Zynq XC7Z045 SoC, 2,4,6 or 8 AD9361 RF transceivers for up to 8 antenna interfaces, 1GB RAM, two 256 Mbit flash, 10GbE, GbE, 1 SD card slot, TCLK A-D, CPRI compression enables up to 3x effective bandwidth

### Ordering Information

|            |  |
|------------|--|
| NAMC-SDR-8 | SDR Module, Zynq XC7Z045, 8 antenna interface, full size |
|------------|--|

# AdvancedMC I/O Modules – JTAG

## NAT-JSM

Flexible testing and diagnostic JTAG Switch Module



JTAG vector testing of all slots in a system, JTAG download via MCH through Ethernet, JTAG programming connector at front panel, target selection through JTAG information, multiple JSM pinout configurations via FPGA, mid size and full size form factor

### Ordering Information

|               |                               |
|---------------|-------------------------------|
| NAT-JSM-FPOSF | JTAG Switch Module, full size |
| NAT-JSM-FPOSF | JTAG Switch Module, mid size  |



# AdvancedMC I/O Modules – Storage

## AMC 600/x0x

1.5 Gbit/s SATA Storage Module with RAID Function



Up to 2.5" SATA HDDs or CompactFlash, 1.5 Gbit/s, RAID 0 or 1, AMC.3, opt. -40°C .. +85°C operating temperature range

### Ordering Information

|                |   |
|----------------|---|
| AMC 600/101-1y | Storage AMC Module, SATA HDD, full size           |
| AMC 600/202-1y | Storage AMC Module, 2 SATA HDDs, double full size |
| AMC 600/302-49 | Storage AMC Module, CompactFlash, mid size        |
| AMC 600/402-1y | Storage AMC Module, 2 SATA HDDs, double mid size  |

## Renice Technology: Reliable FLASH memory modules for industrial and safety-critical applications



The Renice Technology storage solutions fit perfectly demands for high reliability and extended operating temperature range. The Renice product offering includes SSD memory modules in 1.8" and 2.5" size with SATA or PATA interface, M.2, ZIF, mSATA, Half Slim SATA, CompactFlash and CFast designs.

More information about Renice: [www.powerbridge.de](http://www.powerbridge.de)

### Flash and SSDs in all form factors

- High performance: continuous write/read access rates up to 500/520 MB/s
- Extreme reliability: MTBF up to 4.000.000 hours
- Safety: Guaranteed data storage of 10 years
- All versions support 128bit encryption
- Robustness: Extended operating temperature range -40°C ... +85°C
- Extreme strength: 2.000 G Shock and 20 G Vibration at 40-2000 Hz
- Secure Delete, and physical self-destruction in military products

# AdvancedMC I/O Modules – Development

## NAMC-EXT

AMC Extender Module



Extender module, management and payload power can separated individually, management power can generated from onboard payload power, -40°C .. +85°C operating temperature range

### Ordering Information

|          |                 |
|----------|-----------------|
| NAMC-EXT | Extender Module |
|----------|-----------------|

## NAMC-EXT-RTM

Extender for AMC Modules



Extender Module for MTCA.4, management and payload power can separated individually, test points for JTAG interface and for soldering additional cables, opt. onboard 3.3V power supply, -40°C .. +85°C operating temperature range

### Ordering Information

|                   |  |
|-------------------|--|
| NAMC-EXT-RTM-F    | Extender Module                            |
| NAMC-EXT-RTM-F-PS | Extender Module, onboard 3.3V power supply |
| NAMC-EXT-RTM-R    | Extender Module for RTM                    |

# AdvancedMC I/O Modules – Development

## NAMC-LM Load Module



Load AMC, DC load simulation 0W to 100W in 10W steps, thermal heat simulation within 3 independent zones, 4 temperature sensors, surveillance and configuration via NATview V2.5, -5°C .. +50°C operating temperature range

### Ordering Information

|           |                            |
|-----------|----------------------------|
| NAMC-LM-F | AMC Load Module, full size |
| NAMC-LM-M | AMC Load Module, mid size  |

## NAMC-MMC-RefDesign Modul Management Controller Reference Board



MMC reference board based strictly on MMC Design Package, temperature and voltage sensors, hot-swap, DC/DC converter (12V to 3.3V), serial interface on the front panel via mini USB, MMC Design Package to implement a fully AMC and IPMI compliant MMCs on customer AMC modules, time and cost saving even before customer hardware becomes available by developing and testing customer MMCs based on MMC Design Package

### Ordering Information

|              |   |
|--------------|---|
| NAMC-MMC-REF | AMC MMC Module, mid size                                  |
| NIPMI-OBJ    | MMC Design Package, royalty-free object code license      |
| NIPMI-SRC    | MMC Design Package, royalty-free source code license      |
| NATview      | Java based GUI for monitoring and control of MTCA-systems |

# AdvancedMC I/O Modules – Misc.

## NAMC-psTimer AMC Fast Timing Module with ps Resolution



Fast timing module, 10ps clock and trigger jitter, 23 programmable outputs, clock and trigger distribution, data words and table distribution via fiber, receivers can recover clock and data, 2 front panel trigger ports and one precision clocks as LVDS signal, up to 255 trigger event numbers, 2.5 .. 650 MHz precision clocks, trigger position with 0 .. 160ms delay and 1ns resolution, trigger width with 0 .. 160ms delay and 10ns resolution

### Ordering Information

|                    |   |
|--------------------|---|
| NAMC-psTimer       | AMC Fast Timing Module, one trigger input, one trigger output, double mid size                              |
| NAMC-psTimer-P     | Mezzanine Submodul for NAMC-psTimer for increasing number of trigger inputs and outputs to a total of fours |
| NAMC-psTimer-RTM-C | RTM with up to 9 additional triggers, double mid size   |
| NAMC-psTimer-RTM-F | RTM with up to 9 additional fibre links, double mid size  |

## GPS180AMC GPS AMC Module for Time Synchronisation



12 channel GPS receiver, ultra stabile quartz, high resolution time synchronisation, RS-232, Micro USB 2.0, AMC.1 type 1

### Ordering Information

|            |                                       |
|------------|---------------------------------------|
| GPS180AMCF | Satellite Clock AMC Module, full size |
| GPS180AMCM | Satellite Clock AMC Module, mid size  |

# MicroTCA – Power Modules

## NAT-PM-AC600

600W AC Power Module



600W MicroTCA power module, protection against short circuit, under voltage, over voltage, and over temperature, 92% efficiency, N+1 and 2+2 redundancy, full HPM support, -5°C .. +55°C operating temperature range

### Ordering Information

|               |  |
|---------------|--|
| NAT-PM-AC600  | 600W AC Power Module, full size        |
| NAT-PM-AC600D | 600W AC Power Module, double full size |

## NAT-PM-AC1000

1000W AC Power Module



1000W MicroTCA power module, protection against short circuit, under voltage, over voltage, and over temperature, N+1 and 2+2 redundancy, full HPM support, -5°C .. +55°C operating temperature range

### Ordering Information

|               |   |
|---------------|---|
| NAT-PM-AC1000 | 1000W AC Power Module, double full size |
|---------------|---|

## NAT-PM-DC600LV

600W Low-Voltage DC Power Module



600W low-voltage DC MicroTCA power module, dual -24V inputs, 16 independent 12V channels for payload power and 3.3V management power, eMMC, output short circuit protection and output over voltage protection, input under voltage shutdown, over temperature protection, fully redundant operation, N+1 redundancy, hot-swap, -5°C .. +50°C operating temperature range

### Ordering Information

|                      |  |
|----------------------|--|
| NAMT-PM-DC600LV-FP0S | 600W LVDC Power Module, MTCA.0 front panel |
| NAMT-PM-DC600LV-FP1D | 600W LVDC Power Module, MTCA.1 front panel |
| NAMT-PM-DCCABL       | Power cable, 24VDC                         |

## NAT-PM-DC1300

1300W DC Power Module



1300W DC MicroTCA power module, input voltage range -40 to -60 V, 16 independent 12V channels for payload power and 3.3V management power, eMMC, output short circuit protection and output over voltage protection, input under voltage shutdown, over temperature protection, fully redundant operation, N+1 redundancy, hot-swap, -5°C .. +50°C operating temperature range

### Ordering Information

|                     |   |
|---------------------|---|
| NAMT-PM-DC1300-FP0S | 1300W DC Power Module, MTCA.0 front panel |
| NAMT-PM-DC1300-FP1D | 1300W DC Power Module, MTCA.1 front panel |
| NAMT-PM-DCCAB       | Power cable                               |

## NAT-PM-DC840

420/840W DC Power Module



420 or 840W DC MicroTCA power module, dual -48V input, protection against short circuit, under voltage, over voltage, and over temperature, 95,5% efficiency, N+1 and 2+2 redundancy, -5°C .. +65°C operating temperature range

### Ordering Information

|               |                      |
|---------------|----------------------|
| NAMT-PM-DC420 | 420W DC Power Module |
| NAMT-PM-DC840 | 840W DC Power Module |

## W-IE-NE-R

1000W Power Module



1000W MTCA.4 power module, USB, ripple & noise (PP) < 10mV, 93% efficiency, 0°C .. +50°C operating temperature range

### Ordering Information

|           |                    |
|-----------|--------------------|
| PS-MTCA.4 | 1000W Power Module |
|-----------|--------------------|



## NATview



### Overview

NATview is an easy to use visualization tool for any MicroTCA system that includes a NAT-MCH. NATview allows the user to view at and manipulate the components of the MicroTCA system in a graphical way. Being operating system independent NATview runs on any host computer that is internal or external to a MicroTCA system and can be started from a USB thumb drive. Thus NATview is ideally suited for any system or support engineer to check and analyze the status of a MicroTCA system.


### Connecting to the MicroTCA system

NATview connects to the NAT-MCH using the Remote Management Control Protocol (RMCP). The RMCP host part is included in NATview, so no additional protocol support is required for the host. The MicroTCA system is identified by the IP address of the NAT-MCH. Once connected to a MicroTCA system, NATview will display a photo-realistic view of the chassis including the inserted Field Replaceable Units (FRU). Moreover, NATview can be configured to periodically update the displayed sensor information.

### Backplane, FRU Editor and HPM Update Manager

The Backplane Viewer allows a user to look at the theoretical and actually established connections in a connected MicroTCA system.


The optional FRU Editor provides the needed tool to manipulate the records contained in the EEPROM of a FRU.



The Hardware Platform Management (HPM) is a standardized protocol to update any programmable part of a FRU in side a MicroTCA system.

NATview can accomodate the personal look-and-feel. Moreover, NATview allows the user to add own images for the photo-realistic display.

## ESD: EtherCAT Master Stack for several (Real-Time) Operating Systems



### Features

- Configuration and management of EtherCAT networks
- Cyclic exchange of process data
- Sophisticated API common to all implementations as interface between the application and the EtherCAT master stack
- Mailbox based communication: CAN application protocol over EtherCAT (CoE) Ethernet over EtherCAT (EoE) File over EtherCAT (FoE) Servo Drive over EtherCAT (SoE)
- Built-in detailed diagnostics and profiling functions
- Written in ANSI-C designed for high performance, small resource usage and scalability
- Core components of the stack software are operating system and CPU architecture independent
- Adaption to many prevalent (real-time) operating systems available from stock
- EtherCAT Master Class A according to ETG.1500

The EtherCAT Master Stack from ESD electronics is designed for high performance, small resource usage and scalability. The core components are operating system (OS) and CPU architecture independent. An adaption to many prevalent (real-time) operating systems is available from stock which guarantees a cost efficient fast time-to-market integration into a custom application.

# AdvancedMC Specification

## AMC Modules

The PICMG Advanced Mezzanine Card (AdvancedMC, AMC, AMC Module) specification describes computer interface cards. The original purpose was to define a follow-on format for PCI mezzanine cards (PMCs) as an in-operation-replaceable mezzanine module for Advanced TCA systems. Subsequently housing systems for the operation of AMC modules were defined with the PICMG MicroTCA specification. They can be plugged in from outside and as such allow maintenance-friendly systems to be developed. AMCs can have any number of functions and as such may be I/O or CPU modules. Table 2 compares the features of AMC modules and PCI cards. As every AMC slot can take a CPU module, multi-processor systems are also easy to implement.

## Module Formats and Front Panels

The AMC circuit board measures 181,5 x 73,8 mm<sup>2</sup>; and is also available in double size 181,5 x 148,8 mm<sup>2</sup>. The compact (3HP), mid-size (4HP) and full-size (6HP) front panel formats allow a total of six module sizes (see figure 2). For example, mid-size or double mid-size formats are referred to. The most common are mid-size or full-size AMC modules.

## Card Interface

The AMC module (see figure 1) has a 170-pin card connector with 20 serial high-speed ports and 5 clock lines. The ports are bi-directional differential pairs and the clock lines are also differential signals. Two leading presence pins are used for controlling the power control function (in the MicroTCA system or on the carrier board). The management interface (I<sup>2</sup>C-Bus) uses two pins, and three pins are used for geographical addressing. There is one enable signal and five JTAG test lines.

The module is powered by a 12 V voltage (payload power, PP) and an additional 3.3 V voltage (management power, MP). A total of eight pins are available for the payload power, one pin for the management power and there are a total of 56 ground wires. The high number of payload power pins allows high supply currents, and as such a maximum module power dissipation of 80 Watt.

## Use of Ports

Various sub-specifications define how the AMC ports are used. The potential protocols are Gigabit and 10 Gigabit Ethernet, PCIe, Serial RapidIO, SATA, SAS and Fibre Channel. Table 1 provides details about the options for use.

## Management

An AMC module communicates with the carrier via IPMI commands. The foundations for the management functions between the carrier and the AMC module are defined in the AdvancedMC and AdvancedTCA specifications. For example, an AMC module provides information about power requirements, supported interfaces

and operating temperature. The management functions allow the module reset, power-on/off and enable also complex operations like e.g. a firmware update.

## Benefits of AMC Modules

The use of AMC modules in industrial computers or their design based on AMC modules has many advantages: Up to 6 (six) PCIe root complexes, high data throughput, protocol diversity, the possibility of high power dissipation, system management and hot-swap make an application future proof and long-lived. The serviceability of AMCs, their long product life cycle and the stability of this industry standards provide safety for investors and keeping the total cost low.

Fig. 1: The AMC module interface to the carrier




Table 1: Use of AMC ports

| Connector Region | AMC Port#         | AMC.1 | AMC.2   | AMC.4  |                  |
|------------------|-------------------|-------|---|--------|------------------|
| Basic Side       | Clocks            | TCLKA |   |        |                  |
|                  |                   | TCLKB |   |        |                  |
|                  |                   | FCLKA |   |        |                  |
|                  | Common Options    | 0     | GbE AMC.2 Typ E1                                      | or     | GbE AMC.2 Typ E2 |
|                  |                   | 1     | unassigned  |        | GbE AMC.2 Typ E2 |
|                  |                   | 2     | AMC.3 SATA/SAS/FC                                     |        |                  |
|                  |                   | 3     | AMC.3 SATA/SAS/FC                                     |        |                  |
| Fat Pipe         | 4                 | Typ 1 | Typ 2   | Typ 4  |                  |
|                  | 5                 |       |   | Typ 8  |                  |
|                  | 6                 |       |   | Typ 6  |                  |
|                  | 7                 |       |   | 10 GbE |                  |
| Extended Side    | Extended Fat Pipe | 8     | Typ 1   | Typ 2  |                  |
|                  |                   | 9     | GbE   | GbE    |                  |
|                  |                   | 10    | GbE   | GbE    |                  |
|                  | 11                | GbE   | 10 GbE  |        |                  |
|                  | Extended Options  | 12-15 | Ports 12 to 15 and 17 to 20 are reserved for rear I/O |        |                  |
|                  | TCLKC/D           |       |   |        |                  |
|                  | 17-20             |       |   |        |                  |

# AdvancedMC Specification

|                     | PCI   | AMC  |
|---------------------|---|--|
| Form factor         | Intern installed, half size, full size, standard or low profile | Front pluggable, double board size possible, 3HP, 4HP, 6HP front panels                                      |
| System architecture | Single master   | Multi master, up to six PCIe root-complexes  |
| Connector           | Direct connector  | Direct connector, harthing connectors  |
| Interconnect        | PCI (66/64)<br>PCI-X (133/64)<br>PCI Express                    | 20 serial high speed ports:<br>1GB/10GB Ethernet<br>Fibre channel, SATA, SAS,<br>PCI Express, Serial RapidIO |
| IPMI                | no  | yes  |
| Hot swap            | Not available, card exchange is a main problem                  | yes  |
| I/O                 | Front or internal I/O   | Front or Rear I/O  |
| Power dissipation   | Cooling is a main problem / 7.5Watt PMC                         | 80 Watt  |

Table 2: Comparison AMC modules and PCI cards

## Standards and Sub-Standards

The AMC standard consists of the basic AMC.0 specification as well as the further AMC.1, AMC.2, AMC.3 and AMC.4 sub-standards. AMC.0 sets out mechanics, layout and pin allocation, AMC.1 describes the pin allocation for PCIe, AMC.2 the pin allocation for 1/10 Gigabit Ethernet. AMC.3 defines SATA/SAS/Fibre Channel and AMC.4 Serial RapidIO.

The current (January 2015) valid AMC standards are:

- PICMG AMC.0 R2.0 Advanced Mezzanine Card Base Specification of 15 November, 2006,
- PICMG AMC.1 R2.0 PCI Express on AdvancedMC of 8 October, 2008,
- PICMG AMC.2 R1.0 Ethernet Advanced Mezzanine Card Specification of 1 March, 2007,
- PICMG AMC.3 R1.0 Advanced Mezzanine Card Specification for Storage of 5 August, 2005,
- PICMG AMC.4 Advanced Mezzanine Card Specification for Serial RapidIO of 9 July, 2009,

A further AMC standard, PICMG ARTM.0 AdvancedTCA Rear Transition Module, is in the definition.







|                | Compact-Size (3HP)  | Mid-Size (4HP)   | Full-Size (6HP)  |
|----------------|---|--|--|
| Single modules | <br>73.8x13.88x181.5mm   | <br>73.8x18.96x181.5mm   | <br>73.8x28.95x181.5mm   |
| Double modules | <br>148.8x13.88x181.5mm | <br>148.8x18.96x181.5mm | <br>148.8x28.95x181.5mm |

Fig. 2: Designs of AMC modules



## The Hot-Swap Mechanism and its Implementation in MicroTCA

Where an AMC module is inserted into a running system, a process is started whose individual steps are described below by way of example.

At first the management controller (on ATCA carrier, MCH or SSM) is notified about the new module via the presence signal. Now the management voltage for this slot is activated allowing the module's inventory to be created. Here, information about the AMC module such as power consumption, name and manufacturer of the module, as well as further information about the physical interfaces (e-keying) is collected by the management controller. This provides it with the necessary information for the protocols used and allows it to activate the corresponding switch connections. Only then is the power supply (12 V, payload power) to the AMC module switched on. During creation of the inventory, the blue hot-swap LED in the front panel flashes. It goes out when the supply voltage is switched on and the AMC module is ready for operation.

When an AMC module needs to be removed during operation, this is first notified by activating the

handle on the front panel. The associated micro-switch sends a signal to the IPMI controller located on the AMC module that in turn notifies the carrier management controller about the initiation of this procedure. This in turn ensures that the respective AMC slot is de-energised. The blue LED flashes during this procedure. Once the procedure is completed, the blue LED on the front panel lights up constantly and the AMC can be safely removed.

When an AMC module fails, the management controller identifies the fault and interrupts the supply voltage to the respective AMC module. The blue hot-swap LED on the front panel lights up constantly and the AMC module can be replaced.

## MicroTCA NG

Currently there is a PICMG working group, working on continuing the MTCA standard, this will include necessary extensions of the current fabrics to state-of-the-art speeds, such as 40/100GbE as well as PCIe Gen.4 and Gen.5. It also tackles higher power dissipation per AMC module, to keep up with the demand of today's customer applications and needs. The work shall be ratified within 2023.



**powerBridge  
Computer Vertriebs GmbH**

**Head office**

Ehlbeek 15a  
30938 Burgwedel, Germany  
Phone +49 5139-9980-0  
Fax +49 5139-9980-49

[info@powerbridge.de](mailto:info@powerbridge.de)  
[www.powerbridge.de](http://www.powerbridge.de)

**powerBridge**  
Computer